

Entry Point Modular

Product Specifications

Collection Name	Foot in the Door II	
Style Number	I0306	
Product Type	Modular	
Construction	Needlebond Diagonal	
Fiber Type	Polyester	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.24 per 10 cm
Stitches Per Inch	11	43.31 per 10 cm
Tufted Pile Height	5/32"	3.97mm
Tufted Yarn Weight	44.5 oz	1,508.81 g/m ²
Finished Pile Thickness	.348"	8.84 mm
Total Thickness	0.348	8.84 mm
Product Size	24" x 24"	60.96 cm x 60.96 cm
Average Density	6091	11.34 kilotex
Square Yards per Box	5.33	
Installation Pattern Repeat	none	
Primary Backing	Woven Synthetic	
Secondary Backing	EcoWorx® Tile	

Performance Specifications

Traffic Class	Heavy (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methenamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	certified glp0520
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods

1/4 Turn



transforming performance.



Environmental Specifications

Recyclability 100% recyclable

Materials

Ingredients

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

Total Recycled Content (by weight)	65 %
Pre-Consumer	41 %
Post-Consumer	24 %
Bio-Based/Rapidly Renewable Content (By Weight)	0 %
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

NSF 140	gold certified
CRI Green Label Plus	certified glp0520
USGBC LEED	contributes

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit patcraft.com/testing for more information.