



Construction specifications

Product	Sideline
Style #	7834
Fiber Content	Masland Solution Dyed nylon
Fiber Weight (tufted)	38 oz./Sq. Yd. (1288 g/m ²)
Construction	Tip Sheared Loop Pattern
Dye Method	Solution Dyed
Gauge	1/10
Pattern Repeat	4"W x 4"L (10.16cm x 10.16cm)
Width	12' (3.66)
Pile Height	.313"/.218"/.156" (7.95 mm/5.54 mm/3.96 mm)
Total Weight	84 oz./Sq. Yd. (2848 g/m ²)

Performance specifications

Flammability Rating:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts / CM ² Class 1.
Smoke Density:	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness	4.0 or better
Static Rating:	Less than 3.5 kV. Antistat warranted for the life of the carpet.
Warranty:	10 year wear warranty
Primary Backing	Non-Woven
Secondary	Woven Polypropylene

Tufted fiber weight denotes specs prior to tip shearing. Tip Shearing removes a small amount of fiber, which will vary slightly by product and production run.

Sideline meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Certification # GLP1678.

All Masland Designs are protected under the U. S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.