

#20 Draft

Manufacturer

Roppe Corporation
1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA 44830-1158
Website - www.roppe.com
t: (419) 435.8546 tf: (800) 537.9527
f: (419) 435.1056
e-mail: sales@roppe.com

Product Description

Roppe Pinnacle Plus sculpted rubber wall base is a true, 100% thermoset (TS) rubber wall base that is PVC free. Pinnacle Plus comes in a variety of profiles and is designed for use in both commercial and residential wall base applications. Available in several heights from 2 1/2" to 5 1/2" Pinnacle Plus wall base is incredibly durable, allowing it to stand up to a wide range of use when compared to vinyl wall base.

Features

PVC and Phthalates Free
Extremely Durable & Flexible
Available in a Wide Variety of Sizes
Will Not Shrink, Gap or Cup
Recyclable (IMPACT Recycling Program)
Qualifies for LEED® Credits
FloorScore® Certified

#20 Draft

Profile:	#20 Draft
Nominal Height:	4" (101.6 mm)
Nominal Thickness:	1/8" (3.2 mm)
Nominal Length:	120' Coils (36.58 m)
Carton Quantity:	1 Coil (120' ft. Total)



#20

Technical Data

LEED v2009 IEQ Credit 4.1: Qualifies
ASTM F1861 - Resilient Wall Base: Type TS, Group 1, Style D
ASTM E648 (NFPA 253) - Critical Radiant Flux: Class I, > 0.45 W/cm2
ASTM E662 (NFPA 258) - Smoke Density: Passes, <450

ASTM E84 - Flammability: Class B
Acclimation Time: 48 hours
Storage & Acclimation Temperature: 65° - 85° F

Adhesives* ([Visit our website for complete Adhesive instructions](#))

AW-510 Acrylic Wet-Set Adhesive

Unit Size: 1 or 4 Gallon Units
VOC: < 0.1 g/l
Coverage Rate: 160 sq. ft. per gallon
Substrate: Porous

WB-600 Acrylic Wall Base Adhesive

Unit Size: 30 oz. Cartridge, 1 Gallon and 4 Gallon Units
VOC: < 12 g/l
Trowel Coverage Rate: 180-340 lin. ft. per gallon
Cartridge Coverage Rate: 30-70 lin. ft. per cartridge
Substrate: Porous

C-630 Contact Adhesive

Unit Size: 1 Quart
VOC: 0.0 g/l
Coverage Rate: 20-40 sq. ft. per unit or 120-140 lin. ft. per unit.
Substrate: Non-Porous

Installation* ([Visit our website for complete Installation instructions](#))

All material is to be delivered to the installation location in its original packaging with labels intact. The installation area, unboxed wall base and adhesive are to be maintained between 65° (19°C) and 85° (30°C) for at least 48 hours before installation, during installation and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. A bond test should be performed at least 72 hours prior to the scheduled installation to ensure the surface is suitable and there should be extreme difficulty in removing the wall base from the surface.

Maintenance* ([Visit our website for complete Maintenance instructions](#))

Pinnacle Plus can be cleaned with a neutral pH cleaner and a soft wet cloth.

Availability, Cost & Samples

Roppe Flooring products are sold through distribution. To locate the nearest distributor, visit www.roppe.com. or send an email to solutions@roppe.com

Technical Document Support

Additional product resources and technical documents are available online at www.roppe.com. For additional technical support, send an e-mail to solutions@roppe.com

Warranty

Roppe Provides a 2 year Limited Warranty on all Pinnacle Plus Wall Base. For additional information, see associated Warranty documents.

***For complete adhesive, installation & maintenance instructions, visit www.roppe.com**