

# Care and Maintenance ■

**DuraLite™**

8/16/13

KI-62191R1

DuraLite tables have been designed to be durable, lightweight and virtually maintenance free.

## **To ensure the longevity of your product we recommend the following steps when it comes to the cleaning of your new tables:**

DuraLite tables are made of durable, long lasting ABS plastic: Although impervious to most liquids and despite its hard surface texture, it does require some careful attention when it comes to cleaning the surface.

Work surfaces can be cleaned with any alcohol based industrial glass cleaner or simply a light soap water mixture. Windex is the recommended option for this product.

For heavy, malicious markings, Simple Green, Clorox spray or other multipurpose glass cleaners coupled with a stiff brush will clean most problem areas. It will be necessary to wipe the table down with Windex afterwards to complete the process.

Using a stiff brush will improve cleaning and remove heavy marks that may have become embedded in the work surface texturing.

Aggressive, solvent based cleaners simply are not necessary to keep your tables looking clean and new. Solvent based products can damage the plastic and should not be used.

### **Do not use these products:**

Solvent based cleaners such as mineral oil, mineral spirits, or turpentine.

Citrus cleaners (all contain high levels of citric acids that penetrate plastic).

Orange Oil based cleaners (all contain citric acid).

Heavy-duty cleaners such as Fantastic, 409 and other aggressive industrial cleaners that are designed for bathrooms and kitchens.

Powdered cleaners such as Ajax or Con Ami.

Heavy, intentional marking by pen or permanent marker may be difficult or impossible to completely remove. Using the above methods will create the best results.

Proper care and careful use is the best method of maintaining the finish of the product.

### **Use**

DuraLite tables are designed for indoor use. Discoloration or fading may occur if used outside or if placed in direct sunlight.

Make sure the legs are completely unfolded and gravity locks are in position before using table.

The top surface and edges of tables should not be dropped onto the floor. In the case of round tables, rolling should be avoided. Dropping or impacting the table surface or edges may cause stress (white) marks or cracks.

When moving tables from one setup position to another, do not drag across the floor. This can cause damage to the legs. Two people should lift tables for movement to a new set-up location or for storage.

Two people are required to load and unload tables from storage racks and table caddies. Dropping the table into the rack or caddy, or onto the floor when removing for setup could



## Care and Maintenance ■

cause cracking or stress marks. When unloading a table, start from outside edge so the second person can move around the table caddy. When loading the table caddy, move the first table toward the center to allow the next table to be loaded.

Proper Handling Techniques below:



### Field-Replaceable Components

**Legs:** The unique metal-to-metal leg attachment allows new legs to be attached in the original threaded mounting holes. Do not over-torque screws.

**Corner Covers:** The exclusive corner cover is designed to remain fastened to the table to protect the top core even during extreme abuse. Should the corner cover need to be replaced from mishandling, follow these simple instructions:

1. Place table upside down on a clean, smooth surface.
2. Locate the identified dimples on the underside of the corner covers (molded-in arrows point to these locations).
3. Drill down through these dimples to a depth of  $\frac{1}{2}$ " with a  $\frac{1}{4}$ " drill bit. Lightly ream the hole with the drill bit to release the damaged corner cover. Be careful not to drill through the top.
4. Remove the old corner cover and two metal spring clips. Attach two new spring clips with a  $\frac{5}{16}$ " hex key. Align & insert the 3 tabs on the spring clip with the 3 grooves in corner molding. When spring clip bottoms, turn clockwise to secure. Attach new corner cover with firm, even pressure.

NOTE: New corner cover replacement kits (which include new spring clips) are available to match the table tops in the following colors.

<u>Color</u>	<u>Order Part #</u>
(GR) Blue Grey	#DLT.CC.TGR
(SA) Sand	#DLT.CC.TSA
(WA) Walnut	#DLT.CC.TWA

(Above part # is for 1 corner cover & 2 new spring clips)