U-Series is an active and accessible storage collection designed to augment KI Systems' configurations and provide more relevant and cost-effective workstations for applications within each of KI's vertical markets.

The U-Series collection includes freestanding, mobile and worksurface-supporting pedestals, double pedestals, credenzas, wardrobe cabinet units, side-access bookshelf wardrobe units, overheads and related accessories. Nominal and actual dimensions are listed with each item to the nearest $1/16$ inch.

Construction and Standard Features

All U-Series storage units are constructed of steel. Box and file drawers feature smooth riding ball-bearing slides. Units feature ADA-compliant nickel-plated loop pulls. Where appropriate, leveling glides allow for adjustability of approximately 1".

U-Series Locks

U-Series storage comes standard with master keyable, P-Series lock cores and can be specified as randomly keyed, without lock core, or keyed alike and are compatible with other KI key-alike storage lines. Wardrobes contain multiple locks but will be keyed alike for each entire unit. Locks are black chromate finished.

U-Series Paint

Units are cleaned thoroughly and subjected to a phosphate etching process before painting with a hybrid epoxy powder paint.

Pedestals

Worksurface-supporting pedestals are used to support worksurfaces in panel-wrapped applications. Cantilevers or other supports are not required at the end of a worksurface supported by a pedestal, but panel supporting brackets must be specified to fill the space between the back of the pedestal and engage into a panel if used as a return panel replacement. Freestanding pedestals feature four non-adjustable glides.

Pedestals are shipped for front-to-back, letter-sized filing. Optional pencil tray, file and box drawer dividers are available.

20"/ 24" Pedestal Construction

Outer shell: 20 gauge top with 16 gauge bottom reinforcement
Drawer front: 22-gauge steel
File Divider: 22-gauge Steel

20" Pedestal Internal Drawer Dimensions

File Drawer:
Internal height: 11"
Internal width: $12^{1}/_{8}$"
Internal depth: $16^{1}/_{4}$"

Box Drawer:
Internal height: $5^{1}/_{8}$"
Internal width: $12^{1}/_{8}$"
Internal depth: $16^{1}/_{4}$"

24" Pedestal Internal Drawer Dimensions

File Drawer:
Internal height: 11"
Internal width: 12"

Box Drawer:
Internal height: 5$\frac{1}{8}$"
Internal width: 12"

Credenzas

Each freestanding credenza features a single sliding door with lock that spans approximately half of the width of the credenza. Bottom shelf is sufficiently sized to hold binders. Top shelf is non-adjustable. Bottom of unit features adjustable glides with approximately 1" of adjustment.

Credenza Construction

Outer wrapper: 20-gauge steel
Middle shelf: 20-gauge material
Bottom: 20-gauge steel
Partition: 20-gauge steel
Top: 20-gauge steel
Top reinforcement: 18-gauge steel
Sliding door: 20-gauge steel

Credenza Clearance Dimensions

Unit depth: 15"
Unit height: 27$\frac{3}{4}$"
Internal width (upper section): 36", 34", 42", 40"
Internal width (lower section): 36", 16$\frac{1}{2}$", 42", 19$\frac{1}{2}$"
Internal depth: 14"
Internal height (upper section): 6"
Internal height (lower section): 15$\frac{1}{8}$"

Wardrobe Towers

Wardrobe towers are stand-alone storage units. Wardrobe/cabinet units feature a pedestal in file/file or box/box/file configuration, a full vertical height wardrobe with coat hook and a front-facing storage cabinet with an adjustable shelf. Wardrobe/side-access bookshelf units feature a pedestal in file/file or box/box/file configuration, a full vertical height wardrobe with coat hook and an open bookcase with one adjustable shelf. Pedestal aesthetic matches wardrobe pedestal. The handedness of a wardrobe tower is determined by the location of the wardrobe unit. A right unit features the wardrobe on the right side of the unit.

Wardrobe Tower Construction
Outer shell: 20-gauge steel
Upright members: 20-gauge steel
Door fronts: 20-gauge steel
Drawer front: 22-gauge steel
Shelves: 20-gauge steel
Tower cap: 20-gauge steel
Tower base: 20-gauge steel
Base reinforcements: 18-gauge steel
Vertical supports: 20-gauge steel

TECHNICAL SPECIFICATIONS (CONTINUED)

Internal Dimensions

File Drawer:
Internal height: 11"
Internal width: 12"

Box Drawer:
Internal height: $5^1/_8$"
Internal width: 12"

Wardrobe:
Internal height: 64": $58^{13}/_{16}$"; 48": $42^{13}/_{16}$"
Internal width: $7^3/_8$"

Bookshelf:
Internal width: $20^7/_{16}$"
Internal depth: $14^{15}/_{16}$"
Shelf thickness: $^3/_4$"
Shelf range of adjustment: $8^1/_4$" on $1^3/_8$" centers

Cabinet:
Internal height: 64": 34"; 48": 18"
Internal width: $13^7/_8$"
Internal depth: 21"
Shelf thickness: $^3/_4$"
Shelf range of adjustment: $8^1/_4$" on $1^3/_8$" centers

Sliding Door Overheads

Each overhead features a single sliding door with lock. Door spans approximately half of the width of the unit. Slide mechanism uses four wheeled rollers. Overhead is sufficiently sized to hold binders.

Overhead Construction

Vertical supports: 16-gauge steel
Horizontal supports: 18-gauge steel
Sliding door: 18-gauge steel

Overhead External Dimensions

External width: nominal dimension less $^1/_4$"
External depth: $14^3/_8$" ($15^1/_2$" with handle)
External height: $14^7/_{16}$"
Door height: $14^3/_8$"

Overhead Clearance Dimensions

Internal width: nominal dimension less $^1/_2$" ($^1/_4$" per side)
Internal depth: $12^1/_2$"
Internal height: $12^1/_2$"

KI

Furnishing Knowledge®