


# ETC330-GB LED

## Inground Luminaires

1/8



**we-ef**



### Description

IP67. Inground LED uplight. Suitable for flush installation in concrete or earth. Offset gimbal mounted lamp module, with lockable aiming, 30° vertical tilt, and 360° horizontal rotation. Special effects can be realized with linear lens, flood lens, or color filters.

# ETC330-GB LED

## Inground Luminaires


2/8



**we-ef**

## Specifications

### Material Specification

Body:	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Lens:	5/8" thick clear tempered glass lens. Max. load 5 tonnes.
Colours:	 Stainless Steel
Gasket:	Silicone rubber gasket
Fasteners:	PCS polymer coated stainless steel
Ingress protection:	IP67
Impact protection:	IK10+
Corrosion protection:	5CE
Surge protection:	1/2 kV
Mounting:	Suitable for flush installation in concrete or earth. Suitable for walk-over and drive-over applications. Suitable Proper drainage and foundation support must be provided.
Listings:	ETL listed. Suitable for wet locations.

### Electrical Specification

Power supply:	Integral [ECG] LED driver provides 120-277 volt range.
Driver / Ballast:	Integral EC electronic converter
Termination:	Factory sealed termination chamber
Cable:	3 feet of flexible 18/3 cable

### Lifetime

LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25°

### Dimming

0-10V available in request. Must be factory fitted.













# ETC330-GB LED

## Inground Luminaires

3/8



### Choices

Light Distributions	Lumens	Wattages	Colour Temperatures	Colours
 symmetric, wide beam [W]	1614	12	 3000 K	 Stainless Steel
 symmetric, medium beam [M]			 4000 K	
 symmetric, very narrow beam [VN]				
 symmetric, very narrow beam, 'sharp cut-off' [VNS]				
 linear spread, medium beam [M]				
 symmetric, narrow beam [N]				
 linear spread, very narrow beam [VN]				
 linear spread, very narrow beam, 'sharp cut-off'				
 wallwash				

# ETC330-GB LED









## Inground Luminaires

4/8



**we-ef**

## Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 symmetric, wide beam [W]	611-3246	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3247	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 symmetric, medium beam [M]	611-3226	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3227	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 symmetric, very narrow beam [VN]	611-3220	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3221	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 symmetric, very narrow beam, 'sharp cut-off' [VNS]	611-3240	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3241	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 linear spread, medium beam [M]	611-3227 611-8038	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3226 611-8038	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 symmetric, narrow beam [N]	611-3220 611-8037	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3221 611-8037	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 linear spread, very narrow beam [VN]	611-3220 611-8038	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3221 611-8038	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
 linear spread, very narrow beam, 'sharp cut-off'	611-3240 611-8038	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>
	611-3241 611-8038	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	15.00	<a href="#">📄 ↗</a>




ETC330-GB LED

Inground Luminaires




5/8



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 wallwash	611-3252	LED-12/12W / 350 mA - 3000 K	1614	electronic gear	5.50	
	611-3253	LED-12/12W / 350 mA - 4000 K	1614	electronic gear	5.50	

Related Families / ETC300-GB

Family		Dimensions	Wattage	Lumen	Links
					<div>Links</div> <div>Download Data Sheet</div>
ETC330-GB LED		9.84	12 W	1614	<div></div> <div></div>

# ETC330-GB LED

## Inground Luminaires


6/8



### Optical Accessories


#### Flood lens

	C1
611-8037 IO-360-ETC130-GB-LED	3.86



#### Honeycomb louvre

	C1
611-7218 IW-ETC130/330-GB-LED	3.86



# ETC330-GB LED

## Inground Luminaires

7/8




### Linear spread lens

C1

611-8038 IO-180 ETC130/330-GB LED

3.94




### ASC Lens

C1

611-7203 ETC330 ASC Lens

6.26



## Electrical Accessories

# ETC330-GB LED

## Inground Luminaires

8/8



### Sealable junction box

	C1	M1	M2
■ 697-8072 Sealable junction box SJB 130	5.75	Ø 0.39	Ø 0.47 - 0.75

