

Master Step Tile Collection



DESIGN

Product Type:	Rubber
Overall Thickness:	3.17 mm (1/8 gauge)
Size:	3', 4', 6' Lengths
Installation Method:	Glue Down
Recommended Adhesive:	Mohawk Ad-777 Adhesive - Regular Traffic, Mohawk AD-535 Epoxy - Heavy Rolling Loads

PERFORMANCE


Construction:	Homogeneous
Static Load:	1,100 PSI (pounds per square inch)
Resistance To Chemicals:	ASTM F 925 - Compliance
Resistance To Light:	ASTM F 1515 - $\Delta E \leq 8.0$
Resistance To Heat:	ASTM F 1514 - $\Delta E \leq 8.0$
Critical Radiant Flux:	ASTM E 648 - > 0.45
Smoke Density:	ASTM E 662 - ≤ 450

SUSTAINABILITY

Certification:	FloorScore® certified
----------------	-----------------------

SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------




RVR120
Onyx Black




RVR123
Midnight Charcoal




RVR133
Polished Pewter




RVR134
Platinum Gray



RVR137
Carriage Gray




RVR140
Sandstone Beige



RVR148
Deep Chestnut



RVR183
Lime Sorbet



RVR190
Blue Willow

Master Step Tile Collection



RVR191
Night Sky