

# USG ASPEN™ BASIC ACOUSTICAL PANELS

USG Aspen™ Basic Acoustical  
Panels/USG Donn® Brand DX\*/DXL™  
Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Random, naturally sculptured appearance offers upscale look without upscale cost.
- Sizes and performance meet most design criteria.
- Suitable for general applications.
- USDA Certified Biobased Product.<sup>4</sup>

## APPLICATIONS

- Schools
- General offices
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

Medium-Textured Panel



# USG ASPEN™ BASIC ACOUSTICAL PANELS

**ORDER SAMPLES/LITERATURE**  
 USG: [samplitt@usg.com](mailto:samplitt@usg.com)  
 fax: 888 874-2348 | [usg.com](http://usg.com)  
 CGC: contact Sales Representative

**TECHNICAL SERVICES**  
 800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL**  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[cgcdesignstudio.com](http://cgcdesignstudio.com)




PRODUCT CERTIFIED  
 FOR LOW CHEMICAL  
 EMISSIONS:  
 UL.COM/GG  
 UL 2818



Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR <sup>2</sup>	Color	Grid Options	VOC Emissions	Recycled Content <sup>1</sup>	Panel Cost
SLT	2'x2'x3/4"	Class A	650	0.55	35	0.87	White	A	Low	42%	\$\$
	2'x4'x3/4"	Class A	651	0.55	35	0.87	White	A	Low	42%	\$\$
SLT <sup>3</sup>	2'x4'x3/4"	Class A	652	0.55	35	0.87	White	A	Low	42%	\$\$

## USG Aspen™ Basic Illusion™ Two/24




The look of 2'x2' panels

## Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available at [productguide.ulenvironment.com](http://productguide.ulenvironment.com).

## A

### USG DX™/DXL™



## Product literature

Data sheet: SC1809

### ASTM E1264 classification

USG Aspen™ Basic: Type III, Form 2, Pattern CDFI  
 USG Aspen™ Basic Illusion™: Type III, Form 2, Pattern CDFIK

### ASTM E84 and CAN/ULC S102 surface-burning characteristics

Class A  
 Flame spread: 25 or less  
 Smoke developed: 50 or less

## Online tools

[usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com)

### Thermal resistance

R-1.7 (3/4" panels)

### Weight

1.43 lb./sq. ft. (Class A)  
 1.67 lb./sq. ft. (Illusion)

### Maximum backloading

See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

### Maintenance

Can be cleaned easily with a soft brush or vacuum.

## Metric sizes available

Contact sales for minimum quantities and lead times.

## Notes

- For details, see LEED report tool at [usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com).
- LR values are shown as averages.
- Panels have a 15/16" routing.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on [biopreferred.gov](http://biopreferred.gov) website.

## Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

## SC1809/rev. 11-16

© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by  
 USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, ASPEN, DONN, DX, DXL, ILLUSION, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

