

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical  
Panels with ClimaPlus™ Performance/  
USG Donn® Brand Finline® DXF™  
Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

Fine-Textured Panel

## FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- USDA Certified Biobased Product.<sup>7</sup>
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

## APPLICATIONS

- Offices
- Classrooms
- Reception/lobby areas
- Hotels
- Conference areas
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

## CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
USG: [samplitt@usg.com](mailto:samplitt@usg.com)  
fax: 888 874-2348 | [usg.com](http://usg.com)  
CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[cgcdesignstudio.com](http://cgcdesignstudio.com)

TECHNICAL SERVICES  
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL 2818

30 YEAR LIMITED SYSTEM  
WARRANTY  
• No Visible Sag  
• Mold/Mildew Protection

10 YEAR  
AVAILABILITY  
4211, 4221, 4231,  
4411, 4421, 4742,  
4744

HRC HIGH RECYCLED  
CONTENT



UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR <sup>2</sup>	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
SQ 	2'x2'x5/8"	Class A	4210	—	35	0.86	White	A,B,C	Low		44%	\$
	2'x4'x5/8"	Class A	4913	—	35	0.86	White	A,B	Low		44%	\$
SQ 	2'x2'x5/8"	Class A	4211	0.50	30	0.86	White	A,B,C	Low		44%	\$
	2'x4'x5/8"	Class A	4411	0.50	30	0.86	White	A,B	Low		44%	\$
SLT 	2'x2'x5/8"	Class A	4221	0.50	35	0.86	White	D	Low		44%	\$
	2'x4'x5/8"	Class A	4421	0.50	35	0.86	White	D	Low		44%	\$
FLB 	2'x2'x5/8"	Class A	4231	0.50	35	0.86	White	E,F,G,H	Low		44%	\$
	2'x4'x5/8"	Class A	4431	0.50	35	0.86	White	E,F,G,H	Low		44%	\$
SQ 	2'x2'x3/4"	Class A	4750	0.60	33	0.86	White	A,B,C	Low		61%	\$
	2'x4'x3/4"	Class A	4751	0.60	33	0.86	White	A,B	Low		61%	\$
SLT 	2'x2'x3/4"	Class A	4752	0.60	35	0.86	White	D	Low		61%	\$
	2'x4'x3/4"	Class A	4753	0.60	35	0.86	White	D	Low		61%	\$
FLB 	2'x2'x3/4"	Class A	4754	0.60	35	0.86	White	E,F,G,H	Low		61%	\$
	2'x4'x3/4"	Class A	4755	0.60	35	0.86	White	E,F,G,H	Low		61%	\$
SLT <sup>4</sup> 	2'x4'x3/4"	Class A	4742	0.50	35	0.86	White	D	Low		61%	\$
ILT <sup>5</sup> 	2'x4'x3/4"	Class A	4744	0.50	35	0.86	White	I,J	Low		61%	\$

### USG OLYMPIA™ MICRO™ PANELS UNPERFORATED

### USG OLYMPIA™ MICRO™ PANELS 50 NRC<sup>6</sup>

### USG OLYMPIA™ MICRO™ PANELS 60 NRC<sup>6</sup>

### USG OLYMPIA™ MICRO™ ILLUSION™ TWO/24 PANELS

#### PATTERNS

#### USG Illusion™ Two/24



The look of 2'x2' panels

#### Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on [usg.com](http://usg.com) and at [productguide.ulenvironment.com](http://productguide.ulenvironment.com).

#### ClimaPlus™ Warranty Performance<sup>3</sup>

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

#### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

#### GRID PROFILE OPTIONS

A USG DX"/DXL™	B USG DXW™	C <sup>7</sup> USG Centricitee™ DXT™	D USG DX"/DXL™	E USG Centricitee™ DXT™	F USG Identitee® DXI™	G USG Finline® DXF™	H USG Finline® 1/8 DXFF™	I USG Centricitee™ DXT™	J USG Identitee® DXI™

#### PHYSICAL DATA/ FOOTNOTES

Product literature  
Data sheet: SC2180

ASTM E1264 classification  
Type III, Form 2, Pattern CE

ASTM E84 and CAN/ULC S102  
surface-burning characteristics

Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

Online tools  
[usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com)

Weight  
0.78-1.03 lb./sq. ft.

Thermal resistance  
R-1.4 (5/8" panels)  
R-1.7 (3/4" panels)

Maximum backloading  
See USG 30-Year Limited System  
Warranty Commercial Applications  
(SC2102).

Maintenance  
Can be cleaned easily with a soft  
brush or vacuum.

#### Notes

- For details, see LEED report tool at [usgdesignstudio.com](http://usgdesignstudio.com).
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102) and ClimaPlus™ Ceilings Certification of Performance (SC2451).
- Panels have 15/16" routing.
- Panels have 9/16" routing.

6. Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.

7. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on [biopreferred.gov](http://biopreferred.gov) website.

#### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 8-19

© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by  
USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

