

# USG TOUCHSTONE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Touchstone™ Acoustical  
Panels with ClimaPlus™  
Performance/USG Donn® Brand  
DX®/DXL™ Acoustical  
Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Panels are scuff and abuse resistant and can withstand day-to-day activity in high traffic areas.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Firecode® product designed to meet life-safety codes.

## APPLICATIONS

- Schools
- General offices
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

Medium-Textured Panel



# USG TOUCHSTONE™ ACOUSTICAL PANELS

## CLIMAPLUS™ PERFORMANCE

**ORDER SAMPLES/LITERATURE**  
 USG: [samplitt@usg.com](mailto:samplitt@usg.com)  
 fax: 888 874-2348 | [usg.com](http://usg.com)  
 CGC: contact Sales Representative

**TECHNICAL SERVICES**  
 800 USG.4YOU (874-4968)


























**FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL**  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[cgcdesignstudio.com](http://cgcdesignstudio.com)



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS:  
 UL.COM/GG  
 UL 2818



### USG TOUCHSTONE™ PANELS

UL Classified													
Edge	Panel Size	Fire Rating <sup>2</sup>	Item No.	NRC	CAC Min.	LR <sup>3</sup>	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Abuse Resistant	Recycled Content <sup>1</sup>	Panel Cost
													
SQ 	2'x2'x5/8"		5893	0.55	35	0.86	White	A,B	Low			51%	\$\$
	2'x4'x5/8"		5894	0.55	35	0.86	White	A	Low			51%	\$\$
SLT 	2'x2'x5/8"		5896	0.55	35	0.86	White	C	Low			51%	\$\$
FLB 	2'x2'x5/8"		5899	0.55	35	0.86	White	D,E	Low			51%	\$\$

#### Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on [usg.com](http://usg.com) and at [productguide.ulenvironment.com](http://productguide.ulenvironment.com).

#### ClimaPlus™ Warranty Performance<sup>4</sup>

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

#### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

#### Firecode®

Abuse Resistant

### GRID PROFILE OPTIONS

A USG DX®/DXLT™	B <sup>5</sup> USG Centricitee™ DXT™/DXLT™	C USG DX®/DXLT™	D USG Centricitee™ DXLT™	E USG Finline® DXLF™

### PHYSICAL DATA/ FOOTNOTES

**Product literature**  
 Data sheet: SC2214

**ASTM E1264 classification**  
 Type III, Form 2, Pattern CEI

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
 Class A  
 Flame spread: 25 or less  
 Smoke developed: 50 or less

**UL Type**  
 FR-83

**Weight**  
 1.0-1.3 lb./sq. ft.

**Online tools**  
[usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com)

**Thermal resistance**  
 R-1.6

**Maximum backloading**  
 See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

**Metric sizes available**  
 Contact sales for minimum quantities and lead times.

#### Notes

- For details, see LEED report tool at [usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com).
- Fire-rated items: see UL design details.
- LR values are shown as averages.
- For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102) and *ClimaPlus™ Ceilings Certification of Performance* (SC2451).
- Maximum 2'x2' with SQ edge panels.

#### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2214/rev. 11-16  
 © 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by  
 USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXLT, DXLF, DXLT, DXT, FINELINE, FIRECODE, TOUCHSTONE, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

