

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Contour Series Abstract Luxury vinyl floor covering with Techtonic protection to deliver unmatched durability in high-traffic areas in a plank design. Suitable for commercial working environments and offices:

- Education – Classrooms, corridors, multipurpose rooms, laboratories, cafeterias, lavatories
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Healthcare – Exam rooms, lobbies, corridors
- Hospitality – Corridors, vending areas, lobbies

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Contour is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32 mil wear layer and state-of-the-art Techtonic protective finish for long term performance.

1.3.2. **Styles:**

- **Contour Series Abstract**
- **Wear layer Thickness:** 32 mil (0.8 mm)
- **Edge treatment:** Square Edge (SE)
- **Overall thickness:** .120" (3 mm)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Static Load Limit** (ASTM F970): 250 psi, $\leq 0.005"$
- 2.3. **Residual Indentation** (ASTM F1914): Passes
- 2.4. **Static coefficient of friction** (ASTM D2047): ≥ 0.5 SCOF
- 2.5. **Dimensional Stability** (ASTM F2199): Passes
- 2.6. **Resistance to Heat** (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.7. **Resistance to Light** (ASTM F1515): $\Delta\Sigma \leq 8.0$
- 2.8. **Chemical Resistance** (ASTM F925): Passes
- 2.9. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 (> 0.45 W/cm²)
- 2.10. **Smoke Density**(ASTM E648): ≤ 450

3. INSTALLATION

See Contour Luxury Vinyl Plank installation instructions for complete details.

3.1 **Adhesives:**

- **Tarkett RollSmart Adhesive:**
Coverage: 350 – 400 sq. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959 Adhesive:**
Coverage:
Porous Substrate: 150-175 sq. ft. per gallon
Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive:**
Coverage:
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 25 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



Contour Series Abstract

Product Specification

SIZE OPTIONS	18" x 18"	6" x 36"	9" x 36"	12" x 36"
Contour® Series Abstract				
Asphalt (PCAS)	•			
Broadcloth (PCBC)	•			
C-Stamped (PCCD)	•			•
Chenille (PCCH)	•	•		
Color Beam (PCBE)	•	•	•	
Color Pop (PCOP)	•	•	•	
Color Weave (PCWE)	•	•	•	
Faux Bois (PCFB)		•	•	
Filament (PCFI)	•		•	•
Illusion (PCIN)	•		•	•
NuGrain (PCNU)*		•		
Outliners (PCOU)	•	•	•	
Rays (PCRS)	•	•		•
Woven Reed (PCWR)	•	•		
Substrate (PCSU)	•		•	•

* Also available in plank sizes 4" x 36" and 6" x 48"

EMBOSS OPTIONS	Frost (FR)	Quarry (QU)	Rough (RG)	Sawn (SW)	Tick (TK)	Pathway (PH)	Passage (PS)
Contour® Series Abstract							
Asphalt (PCAS)		•				S	
Broadcloth (PCBC)	•	S					
C-Stamped (PCCD)		•					S
Chenille (PCCH)	•	S					
Color Beam (PCBE)	•	S					
Color Pop (PCOP)	•	S					
Color Weave (PCWE)	•	S					
Faux Bois (PCFB)					S		
Filament (PCFI)					S		
Illusion (PCIN)	•	S					
NuGrain (PCNU)		•	•		S		
Outliners (PCOU)	•	S				•	
Rays (PCRS)	S	•			•		
Woven Reed (PCWR)	•	S					
Substrate (PCSU)	•	S					

S = Standard

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 800.899.8916
 info@tarkettna.com

www.tarkettna.com