

## ENVIRONMENTAL PRODUCT DECLARATION

# ULTRALOC BROADLOOM CARPET WITH ECOSOLUTION Q® FACE FIBER



Ultraloc Broadloom Carpet is a high performing, cost effective broadloom option for heavy demand environments.

**shaw** contract group®

We design products that empower our clients to create safe, sustainable, enduring spaces.

We are not trying to get to zero - our goal is more than zero. By adhering to Cradle to Cradle design principles, our goal is not to do less bad, but to do more good.

We don't focus on just one attribute, because this doesn't help our clients or the planet. It all matters - and we're taking every detail into account.

This is our philosophy and it permeates throughout our entire company. The *Cradle to Cradle Certified™* Product Standard holds us accountable to this commitment while supporting our drive for continuous improvement. All while contributing to the circular economy.



# ENVIRONMENTAL PRODUCT DECLARATION

shaw contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025 and EN 15804

This declaration is an environmental product declaration (EPD) in accordance with ISO 14025. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. Accuracy of Results: EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. Comparability: EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. EPDs from different programs may not be comparable.



PROGRAM OPERATOR	UL Environment
DECLARATION HOLDER	Shaw Industries, Inc.
DECLARATION NUMBER	4787366550.123.1
DECLARED PRODUCT	Ultraloc with EcoSolution Q
REFERENCE PCR	IBU and UL Environment. PCR for Building-Related Products and Services – Part A: Calculation Rules for the LCA and Requirements Project Report, (IBU/UL E, V1.2, 03.04.2013, and V1.3, 06.19.2014) IBU. Part B: Requirements on the EPD for Floor Coverings (IBU, V1.6, July 30, 2014) UL Environment: Part B Addendum: IBU PCR for Floor Coverings (UL E, V1.0 Aug 27, 2014)
DATE OF ISSUE	April 1, 2016
PERIOD OF VALIDITY	5 Years
CONTENTS OF THE DECLARATION	Product definition and information about building physics Information about basic material and the material's origin Description of the product's manufacture Indication of product processing Information about the in-use conditions Life cycle assessment results Testing results and verifications
The PCR review was conducted by:	UL Environment Review Panel Thomas Gloria (Chairperson)
This declaration was independently verified in accordance with ISO 14025 by Underwriters Laboratories <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL	<i>Britt Willingham</i> Britt Willingham
This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:	<i>Thomas Gloria</i> Thomas Gloria

This EPD conforms with EN 15804

# ENVIRONMENTAL PRODUCT DECLARATION

**shaw** contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## Product

### Product Description

The product is a commercial broadloom carpet with EcoSolution Q face fiber on the Ultraloc backing system. EcoSolution Q face fiber is nylon 6 with 25% post-industrial recycled content. The face fiber is tufted into a primary backing sheet, latex is added to hold in the fiber, and a woven secondary backing layer is added.

This declaration covers all products consisting of Ultraloc Broadloom Carpet backing and EcoSolution Q face fiber, with face weights ranging from 9 oz per sq. yd. (osy) to 55 osy, and a weighted average face weight of 27.0 osy.

### Application

The product is intended to be used in all commercial settings.

A United States equivalent to *EN 1307: 2008, Textile floor coverings – Classification of pile carpet* does not exist.

### Technical Data

Name	Value	Unit
Product Form	Broadloom	-
Type of Manufacture	Tufted	-
Yarn Type	Nylon 6	-
Secondary Backing	Polypropylene	-
Total Carpet Weight	2194 (avg)	g/m <sup>2</sup>
Total Pile Weight	915 (avg)	g/m <sup>2</sup>
Radiant Panel	Class I	-
NBS Smoke	<450	-
Green Label Plus (indoor air quality)	GLP 2271	-

Table 1: Constructional Data

### Delivery Status

Ultraloc Broadloom Carpet carpet is available to the customer in 12 ft wide rolls.

# ENVIRONMENTAL PRODUCT DECLARATION

**shaw** contract group®

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## Base Materials

Component	Material	Mass %
Face Yarn	Nylon 6	43
	Post-industrial Nylon 6	
Primary Backing	Polypropylene	5
Precoat	Adhesive Copolymer	49
	Calcium Carbonate	
	Aluminum Trihydrate	
Secondary Backing	Polypropylene	3

Table 2: Base materials

## Manufacture

Ultraloc Broadloom Carpet is made with Shaw's Eco Solution Q® Nylon 6 face fiber.

Nylon 6 face fiber is produced internally at Shaw through polymerization from caprolactam. The EcoSolution Q® Nylon 6 fiber is turned into yarn through a variety of processes depending upon the desired look of the finished product.

The yarn is tufted into the primary backing layer, after which a performance precoat is applied to ensure maximum tuft bind, followed by the application of a woven polypropylene secondary backing layer.

## Environmental, Health, & Safety During Manufacturing

Ultraloc Broadloom Carpet is manufactured in the US in ISO 9001 & ISO 14001 equivalent facilities.

Shaw strives to adhere to all applicable laws regarding labor, discrimination and harassment, wages and benefits, health and safety, diversity, and equal opportunity. Through associate engagement, structured safety processes, and a commitment to responsible materials sourcing, Shaw works to improve standards for personal and organizational safety every day. Our programs include:

- Shaw Behavior Based Safety Program to ensure continuous training, awareness, education and safety of all Shaw associates and visitors to Shaw facilities.
- Supply chain, raw materials and waste management programs
- ANSI/NSF 140 compliance
- Shaw Management System (SMS) - Based on ISO 9001 and 14001, and OSHAS 18001 standards, SMS brings together Shaw's Quality, Total Productive Manufacturing (TPM), Environmental, Health and Safety systems under one umbrella, providing associates with a "one stop shop" for helping ensure all job steps are followed the same way every time.



# ENVIRONMENTAL PRODUCT DECLARATION

shaw contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## Reference Service Life

While the service life of floor coverings strongly depends on the location of installation and adherence to cleaning and maintenance instructions given by the manufacturer, the reference service life chosen for this study is 10 years, based on warranty and testing information.

## Extraordinary Effects

In the event of a flooding situation, the flooring shall be thoroughly dried and can be used as normal, with no impact on the environment. When carpet is mechanically destroyed, there are no impacts on the environment.

## LCA: Calculation Rules

### Declared Unit

Name	Value	Unit
Declared Unit	1	m <sup>2</sup>
Conversion Factor to 1 kg	0.4561	-
Mass (average product)	2.19	kg/m <sup>2</sup>

Table 3: Declared Unit

### System Boundary

The EPD is considered to be Cradle-to-Grave.

The following modules are declared: A1-A3, A4, A5, B1, B2, C2, C3, C4.

#### A1-A3 Product Stage

All production-related raw materials and emissions are included from cradle-to-gate, including: energy supply and production, raw material extraction and processing, transport of materials to manufacturing site, packaging materials and transport (including recycled corrugated boxes and cores and plastic film), water use and treatment, and waste processing or recycling of manufacturing and packaging waste.

#### A4 Transport

Transportation of the finished flooring from the manufacturing site to the installation site was included.

#### A5 Installation

Impacts from the installation of the flooring were calculated, including: production and transport of installation materials, waste processing or recycling of installation waste.

#### B1 Use

Indoor emissions during the use stage. No product-related emissions are relevant due to known VOC decay curves and Indoor Air Quality testing (Green Label Plus). No health-related concerns are present during the normal use of the flooring.



# ENVIRONMENTAL PRODUCT DECLARATION

**shaw** contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## B2 Maintenance

Cleaning of the flooring over its lifetime, according to the reference service life. This includes vacuuming and hot water extraction according to the manufacturer's guidelines.

## C2 Transport to End of Life

Transportation of the flooring to an end-of-life facility is included. As a conservative estimate, it is assumed the flooring goes to a landfill at the end of life.

## C3 Waste Processing

As it is assumed the flooring will go to landfill, there is no additional waste processing needed.

## C4 Disposal

For the purposes of this LCA, it is assumed all of the flooring at the end of its useful life will go to the landfill, and the impacts from landfill disposal are included.

## Cut-off Criteria

A cut-off criteria was used as per the PCR, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. This is defined as less than 1% of renewable and non-renewable primary energy usage and less than 1% of the total mass of a unit process, the sum of which shall not exceed 5% of the energy usage and mass.

## Background Data and Quality

All upstream data have been taken from the GaBi 2014 LCI database, version 6.110, using GaBi ts software, compilation 7.0.0.19. All manufacturing data has been collected from Shaw facilities for calendar year 2014.

To ensure the highest quality data, first-hand data was collected by Shaw facilities, and consistent background LCI data from the GaBi 2014 database was used where data could not be collected.

## Allocation

In module A1-A3, allocation was used in the calculation of the recycled content of the fiber and backing material. The recycled content of the fiber comes from the total mass of recycled content used from all fiber facilities for a year divided by the total amount of fiber with the recycled content claim for a year. The recycled content of the backing comes from the total mass of recycled content used in the backing for a year divided by the total backing weight used for a year.

## Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to EN 15804 and the building context, respectively the product-specific characteristics of performance, are

# ENVIRONMENTAL PRODUCT DECLARATION

**shaw** contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

taken into account.

## Estimates and Assumptions

For the purposes of this EPD, the weighted average of the fiber weight over a year's worth of sales data is used. When immediate LCA dataset matches to raw materials were missing, an appropriate similar material was chosen, using the more conservative, higher impact dataset when multiple similar materials were found.

## LCA: Scenarios and additional technical information

The following tables refer to the declared modules and can be used for developing specific scenarios in the context of a building assessment. All indicated values refer to the declared functional unit.

Name	Value	Unit
Transport to the construction site (A4)		
Liters of fuel	38.4	l/100km
Transport Distance	1000	km
Capacity utilization	85	%
Installation in the building (A5)		
Auxiliary Material	0.244	kg
Material Loss	0.22	kg
Broadloom installation requires site testing and conditioning for moisture and alkalinity, proper preparation of the floor, and an adhesive applied with the appropriate trowel, as defined in the installation guidelines found on the manufacturer's website.		
Maintenance (B2)		
Hot Water Extraction Cycle	2	1/year
Hot Water Extraction Cycle (per RSL)	20	1/RSL
Vacuum Cleaning Cycle	4	1/wk
Vacuum Cleaning Cycle (per RSL)	2080	1/RSL
Water Consumption	0.04	m <sup>2</sup> /RSL
Electricity Consumption	6.76	kWh/RSL
End of Life (C2-4)		
Collected as mixed construction waste	2.19	kg
Landfilling	2.19	kg
Reference Service Life		
Reference Service Life	10	years

# ENVIRONMENTAL PRODUCT DECLARATION

shaw contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## LCA: Results

The results found in this EPD are for 1 m<sup>2</sup> of flooring over the reference service life of the product.

Description of the System Boundary (X=included in LCA; MND = module not declared)

Product Stage			Construction Process Stage		Use Stage							End-of-Life Stage				Benefits and Loads Beyond the System Boundaries
Raw Material Supply	Transport	Manufacturing	Transport	Construction-installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy Use	Operational Water Use	De-construction demolition	Transport	Waste Processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
	X		X	X	X	X	MND	MND	MND	MND	MND	MND	X	X	X	MND

## Results of the LCA – Environmental Impact: 1 m<sup>2</sup> of flooring over RSL of product

Methodology	Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3	C4
CML	ADPE	kg Sb eq.	5.87E-06	4.18E-08	9.66E-07	0.00E+00	7.50E-07	1.13E-09	0.00E+00	1.31E-08
	ADPF	MJ	2.36E+02	4.45E+00	1.64E+01	0.00E+00	5.24E+01	1.20E-01	0.00E+00	4.62E-01
	AP	kg SO <sub>2</sub> eq.	3.24E-02	1.04E-03	1.38E-03	0.00E+00	1.48E-02	2.80E-05	0.00E+00	2.15E-04
	EP	kg (PO <sub>4</sub> ) <sup>3-</sup> eq	3.70E-03	2.64E-04	1.78E-04	0.00E+00	1.12E-03	7.12E-06	0.00E+00	2.94E-05
	GWP	kg CO <sub>2</sub> eq	1.38E+01	3.22E-01	7.10E-01	0.00E+00	4.56E+00	8.70E-03	0.00E+00	3.54E-02
	ODP	kg CFC11 eq	2.14E-09	1.99E-12	9.18E-10	0.00E+00	1.61E-09	5.38E-14	0.00E+00	5.65E-13
	POCP	kg ethane eq	3.28E-03	1.29E-04	1.84E-04	0.00E+00	9.22E-04	3.47E-06	0.00E+00	2.01E-05
TRACI	AP	kg SO <sub>2</sub> eq	3.41E-02	1.34E-03	1.42E-03	0.00E+00	1.41E-02	3.63E-05	0.00E+00	2.34E-04
	EP	kg N eq	2.12E-03	1.28E-04	1.29E-04	0.00E+00	1.21E-03	3.46E-06	0.00E+00	2.03E-05
	GWP	kg CO <sub>2</sub> eq	1.38E+01	3.22E-01	7.10E-01	0.00E+00	4.56E+00	8.70E-03	0.00E+00	3.54E-02
	ODP	kg CFC11 eq	2.27E-09	2.12E-12	9.77E-10	0.00E+00	1.71E-09	5.72E-14	0.00E+00	6.01E-13
	Smog	kg O <sub>3</sub> eq	4.91E-01	4.18E-02	2.21E-02	0.00E+00	1.26E-01	1.13E-03	0.00E+00	4.50E-03
caption	ADPE = abiotic depletion potential for non-fossil resources; ADPF = abiotic depletion potential for fossil resources; AP = acidification potential; EP = eutrophication potential; GWP = global warming potential; ODP = ozone depletion potential; POCP = Smog = formation of tropospheric ozone photochemical oxidants									

# ENVIRONMENTAL PRODUCT DECLARATION

shaw contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## Results of the LCA – Resource Use: 1 m<sup>2</sup> of flooring over RSL of product

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3	C4
PERE	MJ	5.30E+00	6.84E-02	4.82E-01	0.00E+00	6.22E+00	1.85E-03	0.00E+00	4.73E-02
PERM	MJ	0.00E+00							
PERT	MJ	5.30E+00	6.84E-02	4.82E-01	0.00E+00	6.22E+00	1.85E-03	0.00E+00	4.73E-02
PENRE	MJ	2.10E+02	4.47E+00	1.70E+01	0.00E+00	6.62E+01	1.21E-01	0.00E+00	4.81E-01
PENRM	MJ	4.52E+01	0.00E+00						
PENRT	MJ	2.55E+02	4.47E+00	1.70E+01	0.00E+00	6.62E+01	1.21E-01	0.00E+00	4.81E-01
SM	kg	1.91E-01	0.00E+00						
RSF	MJ	0.00E+00							
NRSF	MJ	0.00E+00							
FW	m <sup>3</sup>	2.75E+00	1.35E-02	3.15E-01	0.00E+00	3.43E+00	3.65E-04	0.00E+00	2.32E-02
caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water								

## Results of the LCA – Output Flows and Waste Categories: 1 m<sup>2</sup> of flooring over RSL of product

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3	C4
HWD	kg	4.72E-05	6.42E-07	4.41E-07	0.00E+00	1.96E-02	1.73E-08	0.00E+00	1.49E-07
NHWD	kg	1.41E-01	1.41E-04	4.20E-03	0.00E+00	5.36E-02	3.80E-06	0.00E+00	2.20E+00
RWD	kg	7.42E-03	7.36E-06	2.16E-04	0.00E+00	5.43E-03	1.99E-07	0.00E+00	7.65E-06
CRU	kg	0.00E+00							
MFR	kg	3.67E-02	0.00E+00						
MER	kg	0.00E+00							
EEE	MJ	0.00E+00							
EET	MJ	0.00E+00							
caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EEE = Exported thermal energy								

# ENVIRONMENTAL PRODUCT DECLARATION

shaw contract group

Ultraloc Broadloom Carpet with EcoSolution Q® Face Fiber  
Commercial Broadloom Carpet

According to ISO 14025

## Interpretation of Results

The majority of the impact of the flooring is contained within the product stage (A1-A3), with the maintenance piece of the use stage (B2) making up most of the remaining impact. Within the product stage, the largest contributor is the face fiber. As the fiber weight of a specific style changes within the specified range, so do the impacts. The higher face weight products have a higher impact than this average, and the lower face weight products have a lower impact than this average.

## References

### **PCR Part A: Calculation Rules for the Life Cycle Assessment and Requirements of the Project Report**

Adapted for UL Environment from the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Version 1.3, 19.06.2014

### **PCR Part B: Requirements on the EPD for Floor Coverings**

From the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Version 1.6, 30.07.2014

### **PCR Part B: Requirements on the EPD for Floor Coverings, Addendum**

PCR Addendum for IBU Part B: Floor coverings. Version 1, 8/27/2014

### **ISO 14025**

DIN EN ISO 14025:2011-10: Environmental labels and declarations – Type III environmental declarations – Principles and procedures

### **EN 15804**

EN 15804:2012-04: Sustainability of construction works – Environmental Product Declarations – Core rules for the product category of construction products