



## Contour Wood & Stone

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Tarkett Contour Series Wood Stone Luxury vinyl floor covering with Techtonic™ protection to deliver unmatched durability in high-traffic areas in a plank design.
- 1.2. **Manufacturer:**  
Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)
- 1.3. **Proprietary Product Description:**
- 1.4.1. **Construction:** Tarkett Contour is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32-mil wear layer and state-of-the-art Techtonic™ protective finish for long term performance. Tarkett's Techtonic™ is a massive shift forward in performance for hard surface floors. Its advanced polyurethane technology is super tough, resisting scratching, abrasions, scuffing and staining.
- 1.3.1. **Styles:**  
Contour Series Wood Stone
- **Finish:** Techtonic™
  - **Wear layer Thickness:** 32 mil (0.8 mm)
  - **Edge treatment:** Square Edge (SE)
  - **Overall thickness:** .120" (3 mm)
  - 11 Wood / 8 Stone Collections

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Flexibility** (ASTM F137): Passes
- 2.3. **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005''$
- 2.4. **Residual Indentation** (ASTM F1914): Passes
- 2.5. **Static coefficient of friction** (ASTM D 2047):  $\geq 0.5$  SCOF
- 2.6. **Dimensional Stability** (ASTM F2199): Passes
- 2.7. **Resistance to Heat** (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.8. **Resistance to Light** (ASTM F1515):  $\Delta\Sigma \leq 8.0$
- 2.9. **Chemical Resistance** (ASTM F925): Passes
- 2.10. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 ( $> 0.45 \text{ W/cm}^2$ )

### 3. INSTALLATION

See Contour Luxury Vinyl Plank installation instructions for complete details.

#### 3.1 Adhesives:

- **Tarkett RollSmart Adhesive:**  
Coverage: 350 – 400 sq. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959 Vinyl Tile Adhesive Coverage:**  
Porous Substrate: 150-175 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 959HM High Moisture Substrate Adhesive**  
Porous Substrate: 125-150 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour Maintenance Instructions for complete maintenance details.

### 6. TECHNICAL SERVICES

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)  
Contact Technical support at (800)-899-8916 or Email: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

### 7. WARRANTY

Limited 25-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)



## Contour Wood & Stone

## Product Specification

WOOD	EMBOSSING					
	Frost (FR)	Natural Grain (NG)	Quarry (QU)	Rough Grain (RG)	Sawn (STDW)	Tick (TK)
<b>Antique Wood (PCAN):</b> 4x36, 6x36, 6x48 – Herringbone, Unidirectional						
0383		STD				
3815, 3816			STD			
0351, 0353, 0357, 0359, 3512				STD		
0301, 0302, 0305, 0306, 3720					STD	
3810, 3811, 3812					STD	
<b>Circa (PCIR):</b> 18x18 – Horizontal, Ashlar, Quarter Turn, Vertical Ashlar 6x36, 6x48, 7.2x48 – Herringbone, Unidirectional 9x36 – Vertical Ashlar						
4526, 4527, 4528			STD			
<b>Exotic Wood (PCEX):</b> 4x36, 6x36, 6x48 – Herringbone, Unidirectional						
3205		STD				
3314				STD		
3210, 3213, 3214, 3301, 3302, 3310, 3311, 3312, 3324, 3625, 3901						STD
<b>Grand Ash (PCGA):</b> 4x36, 6x36, 6x48 – Herringbone, Unidirectional						
3632, 3634, 3635				STD		
<b>Heartwood (PCHW):</b> 18x18 – Horizontal, Ashlar, Quarter Turn, Vertical Ashlar 6x36, 6x48, 7.2x48 – Herringbone, Unidirectional						
4520, 4521, 4522			STD			
<b>Modern Wood (PCMD):</b> 4x36, 6x36, 6x48 – Herringbone, Unidirectional						
0361, 3306		STD				
3820, 3821, 3822				STD		
3823, 3824, 3825				STD		
3602, 3604, 3606, 3610, 3732, 3104						STD
<b>NuGrain (PCNU):</b> 4x36, 6x36, 6x48 – Herringbone, Unidirectional						
3710, 3712, 3715, 3717						STD
<b>Spalted (PCSP):</b> 6x36, 6x48, 7.2x48 – Herringbone, Unidirectional 9x36 – Vertical Ashlar						
4523, 4524, 4525		STD				
<b>Townhall (PCTH):</b> 4x36, 6x36, 6x48 – Herringbone, Unidirectional						
4505, 4506, 4507, 4508				STD		
<b>Wildwood (PCWD):</b> 6x36, 7.2x48 – Herringbone, Unidirectional 12x36 – Vertical Ashlar						
4200, 4206, 4210, 4212				STD		
<b>Yakisugi (PCYK):</b> 6x36, 6x48, 7.2x48 – Herringbone, Unidirectional						
4500, 4502						STD

STONE	EMBOSSING			
	Fresco (FC)	Frost (FR)	Pathway (PH)	Quarry (QU)
<b>Concrete (PCCN):</b> 18x18, 36x36 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x24 – Vertical Ashlar				
0710, 0712, 0718				STD
7241, 7243			STD	
<b>Fossil Stone (PCFS):</b> 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x24 – Vertical Ashlar				
0830, 0834				STD
<b>Legacy Stone (PCLE):</b> 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x24 – Vertical Ashlar				
0553, 0557			STD	
0541				STD
<b>Modern Stone (PCMS):</b> 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x24 – Vertical Ashlar				
0604, 0606, 0610, 0612, 0614, 0616, 0620, 0624, 0630, 0631, 0632, 0633				STD
<b>Passageway (PCPA):</b> 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar				
0840, 0841, 0842			STD	
<b>Rust Rings (PCRR):</b> 18x18, 36x36 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 6x36 – Herringbone, Unidirectional 12x24 – Vertical Ashlar				
4321, 4323, 4325, 4327			STD	
<b>Solstice (PCSO):</b> 18x18, 36x36 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 6x36 – Herringbone, Unidirectional 12x24 – Vertical Ashlar				
4422, 4424, 4426, 4434			STD	
<b>Vestige (PCVE):</b> 18x18 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x24 – Vertical Ashlar				
1018, 1019				STD

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear, and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)