



MOSAIC

RETRO ROUNDS™  
GLAZED PORCELAIN



 daltile®  
IMAGINE WHAT'S POSSIBLE™



# RETRO ROUNDS™

GLAZED PORCELAIN

## A Modern Take on Your Favorite Retro Look

Nostalgic with a contemporary twist, Retro Rounds brighten up walls, backsplashes and even pool linings. From Cherry Red and Orange Soda to Cobalt Circle and Daffodil Yellow, 13 vibrant colors make up this delightful collection including a classic polka dot option. Complementary matte finishes extend this retro look to the floor.

- GREAT FOR CONTEMPORARY OR TRADITIONAL SPACES
  - Mix of classic and contemporary colors
  - Timeless penny round shape
- MULTITUDE OF OPTIONS
  - Available in gloss and matte finishes for use on the floor and wall
  - Beautiful color varieties to match any space

### MOSAIC

#### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PG

GLAZED PORCELAIN

LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

### SPECIAL FEATURES

Above and cover photos feature Retro Rounds™ Saddle Brown on the wall.



SIZES:



1 x 1 Penny Round  
Mosaic Solids



1 x 1 Penny Round  
Mosaic Patterns

FINISHES: MATTE | GLOSSY


GLOSSY




BOLD WHITE GLOSS RR01




CREAM SODA RR05




SADDLE BROWN RR06




DAFFODIL YELLOW RR07




ORANGE SODA RR08



CHERRY RED RR09




DENIM BLUE RR10




COBALT CIRCLE RR11



SMOKY GRAY RR12



ENGINE GRAY RR13




CANVAS BLACK GLOSS RR14

MATTE




BOLD WHITE MATTE RR02




CANVAS BLACK MATTE RR15

PATTERN MOSAICS



POLKA DOT GLOSS RR03



POLKA DOT MATTE RR04



WATERPROOF



STAINPROOF



SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT\*  
\*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™



VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# RETRO ROUNDS™

GLAZED PORCELAIN

MOSAIC

## SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	1 x 1 Penny Round Mosaic Solids (Mesh-mounted on a 12 x 12 sheet)	(12-7/16" x 11-9/16" Sheet) (31.60 cm x 29.40 cm Sheet)	3/16"	10.00	10
	1 x 1 Penny Round Mosaic Patterns (Mesh-mounted on a 13 x 12 sheet)	(13-1/4" x 11-9/16" Sheet) (33.60 cm x 29.40 cm Sheet)	3/16"	10.63	10

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltille.com/DCOF](http://daltille.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

\*Only matte colors suitable for residential and light commercial floors not subject to outside foot traffic

\*\*Darker colors may show scratches. Only matte colors recommended for counter use.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
----------------------------	-----------------

Approximately 1/8"

 Low (V1)

## TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 250 lbs.
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

## NOTES

**Manufacturer Advisory:** These tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at [daltille.com/Factors](http://daltille.com/Factors).

**ZEROTOX**  
Healthy Homes | Healthy Planet

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of  
Daltille® products and information,  
visit our website at [daltille.com](http://daltille.com).

 **daltille®**  
IMAGINE WHAT'S POSSIBLE™  
©2021 Daltille (3/21)