



## Andros #G0015

## Product Specification

Face Construction	Imperial	Metric
Construction	Tufted Patterned Loop	
Face Weight	31 oz/sq yd	1050.9 g/sq m
Gauge	1/10	39.4 rows/10 cm
Stitches per Inch	8.4	33.1 pu/10 cm
Tuft Density	84 tufts/sq in	13.0 tufts/sq cm
Pile Height Average	0.187 inch	4.7 mm
Pile Thickness	0.099 inch	2.5 mm
Density Factor	11,273 oz/cu yd	417.1 kg/cu m
Fiber System	TDX Nylon	
Dye Method	Solution Dyed	
Fluorine-Free Soil Protection	Eco-Ensure	10.5 Kilotex
Primary Tufting Substrate	Synthetic Non-Woven	
Pattern Match	Not Required	

### Third Party Environmental Certifications

Product	Recycled Content*	NSF 140	Cradle to Cradle
	Overall	SCS Certified	Certified™ v3.1**
Certified ethos® Modular with Omnicoat Technology®	47-75%	28%	Platinum Silver

\*Minimum recycled content certified by Scientific Certification Systems (SCS) and varies by product style.

\*\*Cradle to Cradle Certified is a certification mark licensed by the Cradle to Cradle Products Innovation Institute

### Product Testing/Information

Antimicrobial Chemicals	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
Electrostatic Propensity	1.0 kV (AATCC 134); Permanent Conductive Fiber
Surface Flammability	Passes CPSC FF 1-70 (ASTM D-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
Smoke Generation	Less than 450 (ASTM E-662)
Colorfastness to Light	≥ 4 after 100 hours (AATCC 16E)
Soil Protection	Application Rate: 2% of Face Weight

### Installation Methods

Wet Spread	Backing specific Tarkett Adhesives
Installation Method	24" x 24" Vertical Ashlar; 18" x 36" and 9" x 36" Vertical Ashlar, Herringbone

### Product Notes

1. Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
2. U.S. Patent numbers: 4,849,267; 6,406,574, US 9,988,760 B2
3. Chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

### Tarkett North America

Technical Services Department  
1735 Cleveland Hwy  
Dalton, GA 30721  
800.248.2878 Fax 706.259.2621  
info@tarkettna.com

[www.tarkettna.com](http://www.tarkettna.com)

© 2021 Tarkett USA Inc. 12/2021



IMPERIAL

METRIC

TEST METHOD

**Warranty:** Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering, & backing resiliency loss.

**ethos® Modular with Omnicoat Technology®**

Total Minimum Recycled Content	51.2%		
Pre-Consumer	20.8%		
Postconsumer	30.4%		
Third Party Certification NSF-140	Platinum		
Cradle to Cradle Certification	Silver (Certification #1904)		
Product Size	24" x 24" Tile	(9" x 36" and 18" x 36" also available)	
Secondary Backing	50% Recycled Content		
Intermediate Layer	Fiberglass Reinforced Sealant		
Product Construction	No Delamination per ASTM D-3936		
Secondary Backing Density	65.0	lbs/cu ft	1041 kg/cu m
Secondary Backing Thickness	0.050	inch	1.3 mm
Total Weight	108.9	oz/sq yd +/-5%	3691.4 g/sq m
CRI Green Label Plus Certification	GLP8320		

SCS Certified total 47-75%  
 SCS Certified  
 SCS Certified  
 SCS Certified  
 Cradle to Cradle Certified™ v3.1

