OUT OF THE SHADOWS

Shadowbox

Modular Tile

Construction
Tufted, Textured Loop

Tile Size
50 cm x 50 cm (19.7" x 19.7")

Yarn Type
Milliken-Certified WearOn® Nylon Type 6,6

Stain Resist / Soil Release
StainSmart®

Dye Method
PrintWorks™ Precision Dyeing

Tufted Face Weight
19 oz/yd² (644.2 g/m²)

Gauge
1/8

Stitches Per Inch
10.3

Tufts
82.4/in² (1,276/100 cm²)

Finished Pile Height
0.13" (3.30 mm)

Finished Pile Thickness
0.08" (2.03 mm)

Average Density (Finished)
8,222

Standard Backing
PVC-Free WellBAC® Comfort Cushion
Available with TractionBack®

Recycled Content by Total Weight
Standard Backing: 36.8% Pre-Consumer, 0.0% Post-Consumer
NSF 140 Platinum Backing Option: 26.8% Pre-Consumer, 10.0% Post-Consumer

Embodied Carbon
16.33 (kg CO_2e)/m²

Nominal Total Thickness
0.32" (8.1 mm)

Nominal Total Weight
95.0 oz/yd² (3,221 g/m²)

Flammability (Radiant Panel ASTM-E-648)
≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662)
≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859
Self-Extinguishing

Lightfastness (AATCC 16E)
≥ 4.0 at 80 Hours

Crocking (AATCC 165)
≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H.,70° F.
≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR)
Severe Traffic End-Use Applications

Recommended Maintenance
MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™
GLP0793, Carpet Category 5Y

Recommended Installation Method(s)
Ashlar

WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Flammability

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

© 2022 Milliken & Company | Made in the USA