



## Contour Series

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Tarkett Contour Series Wood Stone Luxury vinyl floor covering with Techtonic™ protection to deliver unmatched durability in high-traffic areas in a plank design.
- 1.2. **Manufacturer:**  
Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)
- 1.3. **Proprietary Product Description:**
- 1.4.1. **Construction:** Tarkett Contour is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32-mil wear layer and state-of-the-art Techtonic™ protective finish for long term performance. Tarkett's Techtonic™ is a massive shift forward in performance for hard surface floors. Its advanced polyurethane technology is super tough, resisting scratching, abrasions, scuffing and staining.
- 1.3.1. **Styles:**  
Contour Series (See below for standard embossing, sizing availability, and packaging info)
- **Finish:** Techtonic™
  - **Wear layer Thickness:** 32 mil (0.8 mm)
  - **Edge treatment:** Square Edge (SE)
  - **Overall thickness:** .120" (3 mm)
  - 13 Collections

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Flexibility** (ASTM F137): Passes
- 2.3. **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005''$
- 2.4. **Residual Indentation** (ASTM F1914): Passes
- 2.5. **Static coefficient of friction** (ASTM D 2047):  $\geq 0.5$  SCOF
- 2.6. **Dimensional Stability** (ASTM F2199): Passes
- 2.7. **Resistance to Heat** (ASTM F1514):  $\Delta\sigma \leq 8.0$
- 2.8. **Resistance to Light** (ASTM F1515):  $\Delta\sigma \leq 8.0$
- 2.9. **Chemical Resistance** (ASTM F925): Passes
- 2.10. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 ( $> 0.45$  W/cm<sup>2</sup>)
- 2.11. **CAN/ULC S102.2:** FSV 160 / SDV 420

### 3. INSTALLATION

See Contour Luxury Vinyl Plank installation instructions for complete details.

#### 3.1 Adhesives:

- **Tarkett RollSmart Adhesive:**  
Coverage: 350 – 400 sq. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959HM High Moisture Substrate Adhesive**  
Porous Substrate: 125-150 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour Maintenance Instructions for complete maintenance details.

### 6. TECHNICAL SERVICES

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)  
Contact Technical support at (800)-899-8916 or Email: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

### 7. WARRANTY

Limited 25-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)

STANDARD EMBOSSING & SIZING AVAILABILITY:

18x18, 36x36 – Quarter Turn, Vertical Ashlar, Horizontal Ashlar 9x36, 12x36 -Vertical Ashlar 6x36 – Herringbone, Unidirectional 18x36 – Vertical Ashlar	STANDARD EMBOSS	SIZES AVAILABLE					
		6x36	9x36	12x36	18x18	18x36	36x36
<b>Collaborative:</b> Create Clarity (PCCT), Create Emphasis (PCCA), Create Expression (PCCP), Create Meaning (PCCS), Create Together (PCCM)	Quarry			•	•		
<b>Mindful Maker:</b> Aquarelle (PCQL), Demure (PCDE), Needle & Thread (PCNT)	Quarry			•	•		
<b>Method</b> (PCMH)	Quarry		•				
<b>PM Square</b> (PCPM)	Quarry				•		
<b>Color Play:</b> Color Beam (PCBE), Color Pop (PCOP), Color Weave (PCWE)	Quarry	•	•		•		
<b>Analog Field</b> (PCAO)	Quarry			•	•		
<b>Aura</b> (PCAU)	Quarry		•		•		
<b>Broadcloth</b> (PCBC)	Quarry				•		
<b>CeraMix</b> (PCCX)	Quarry	•					
<b>Chenille</b> (PCCH)	Quarry	•			•		
<b>Crafted Cane</b> (PCCC)	Quarry	•		•			
<b>Drop Cloth</b> (PCDC)	Quarry		•		•		
<b>Entwine</b> (PCEN)	Quarry		•				
<b>Factor</b> (PCFC)	Quarry	•			•		
<b>Faux Bois</b> (PCFB)	Tick	•	•				
<b>Felt</b> (PIFE)	Quarry	•			•	•	
<b>Fiber Effect</b> (PCFT)	Quarry		•		•		
<b>Filament</b> (PCFI)	Tick		•	•	•		
<b>Foil</b> (PIFO)	Quarry	•			•	•	
<b>Foliate</b> (PCFO)	Quarry		•		•		
<b>GeoGrid</b> (PCGE):	Pathway	•		•	•	•	•
<b>Glint</b> (PCGI)	Quarry			•			
<b>Illusion</b> (PCIN):	Quarry		•	•	•		
<b>Marble</b> (PIMA)	Quarry	•			•	•	
<b>Meshwork</b> (PCGF)	Quarry			•	•		
<b>Mindset</b> (PCMM)	Quarry			•	•		
<b>Mirage</b> (PCMI)	Quarry		•		•		
<b>Outliners</b> (PCOU)	Quarry	•	•		•		
<b>PM Square</b> (PCPM)	Quarry				•		
<b>Polyomino</b> (PCPY)	Quarry			•	•		
<b>Ribweave</b> (PIRI)	Quarry	•			•	•	
<b>Riverbend</b> (PCRB)	Quarry			•	•		
<b>Substrate</b> (PCSU):	Quarry		•	•	•		
<b>Texterran</b> (PCTE)	Quarry		•		•		
<b>Woven Reed</b> (PCWR):	Quarry	•			•		

WOOD:	EMBOSSING					
	Frost (FR)	Natural Grain (NG)	Quarry (QU)	Rough Grain (RG)	Sawn (STDW)	Tick (TK)
4x36, 6x24, 6x36, 6x48, 7.2x48 – Herringbone, Unidirectional						
9x36 – Vertical Ashlar						
Hexagon, Triangle - Random						
<b>Antique Wood (PCAN) 4x36, 6x36, 6x48, 6x24, Hexagon, Triangle</b>						
3815, 3816			STD			
3810, 3811					STD	
<b>Modern Wood (PCMD) 4x36, 6x36, 6x48, 6x24, Hexagon, Triangle</b>						
All colors				STD		
<b>Spalted (PCSP) 6x36, 9x36, 6x48, 7.2x48, 6x24, Hexagon, Triangle</b>						
All Colors		STD				
<b>True To Form Woods:</b>						
<b>Artful Oak (PCMK), Branched Oak (PCBR), Chronical Oak (PCCL), Medley Maple (PCEM), Natural Walnut (PCWT), Proper Oak (PCPO), Wetland Cypress (PCCY)</b>						
6x36, 6x48, 6x24, Hexagon, Triangle						
All Colors						STD
<b>True To Form: Wildcraft Maple (PCWC)</b>						
6x36, 6x48, 6x24, Hexagon, Triangle						
All Colors		STD				
<b>Townhall (PCTH) 6x36, 9x36, 6x48, 7.2x48, 6x24, Hexagon, Triangle</b>						
All Colors				STD		
<b>Wildwood (PCWD) 6x36, 7.2x48, 12x36, 6x24, Hexagon, Triangle</b>						
All Colors				STD		

STONE:	EMBOSSING			
	Fresco (FC)	Frost (FR)	Pathway (PH)	Quarry (QU)
18x18, 36x36 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar				
12x24, 12x36, 9x36 – Vertical Ashlar				
6x36, 6x24 – Herringbone, Unidirectional				
Hexagon, Triangle – Random				
<b>Arterra (PCAT) 6x36, 6x24, Hexagon, Triangle</b>				
All colors				STD
<b>Artifice (PCAR) 18x18, 12x36, 6x24, Hexagon, Triangle</b>				
All colors				STD
<b>Carrera &amp; Carrera Accent (PCRA)</b>				
18x18, 12x36, 6x24, Hexagon, Triangle				
All colors				STD
<b>Metamorphic (PCMP) 9x36, 6x24, Hexagon, Triangle</b>				
All colors				STD
<b>Metamorphic (PCMP) 9x36, 6x24, Hexagon, Triangle</b>				
All colors				STD
<b>Modern Stone (PCMS) 12x24, 18x18, 6x24, Hexagon, Triangle</b>				
All colors				STD
<b>Parisian (PCPR) 18x18, 12x36, 6x24, Hexagon, Triangle</b>				
All colors				STD
<b>Passageway (PCPA) 18x18, 6x24, Hexagon, Triangle</b>				
All colors			STD	
<b>Rust Rings (PCRR)</b>				
18x18, 6x36, 12x36, 18x36, 36x36, 6x24, Hexagon, Triangle				
All colors			STD	
<b>Solstice (PCSO)</b>				
18x18, 6x36, 12x36, 18x36, 36x36, 6x24, Hexagon, Triangle				
All colors			STD	
<b>True To Form Stone:</b>				
<b>Castlerock Sandstone (PCSN), Ebbing Travertine (PCET), Melded Concrete (PCMC), Mineral Basalt (PCMB), Native Soapstone (PCAV), Palladian (PCPD)</b>				
6x36, 12x36, 18x18, 6x24, Hexagon, Triangle				
All colors				STD

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear, and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

## Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)

PACKAGING INFORMATION:

	Size	Pcs Per Carton	Sqft. Per Carton	Lbs. Per Carton	Cartons Per Pallet
Tile	12" x 12" (30.48 x 30.48 cm)	45	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	54
	12" x 18" (30.48 x 45.72 cm)	30	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	12" x 24" (30.48 x 60.96 cm)	18	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	72
	12" x 36" (30.48 x 91.44 cm)	15	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	18" x 18" (45.72 x 45.72 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	18" x 36" (45.72 x 91.44 cm)	10	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	40
	9" x 36" (22.86 x 91.44 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	36" x 36" (91.44 x 91.44 cm)	10	90 (8.4 m <sup>2</sup> )	90 (40.8 kg)	20
Planks	4" x 36" (10.16 x 91.44 cm)	45	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	40
	6" x 36" (15.24 x 91.44 cm)	24	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	66
	6" x 48" (15.24 x 121.92 cm)	18	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	72
	7.2" x 48" (18.29 x 121.92 cm)	15	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	60
Hexagon	12" x 13.8" (30.48 x 35.05 cm)	20	17.3 (1.61 m <sup>2</sup> )	17.3 (7.8 kg)	52
Triangle	6.9" (17.5 cm)	120	17.32 (1.61 m <sup>2</sup> )	17.3 (7.8 kg)	52