

Verastone, Verastone Plus, Trendstone & Trendstone Plus Shapes and Sizes

Note: Not all sizes are shown in this brochure. Please consult your nearest manufacturing facility.

Metric Shapes and Sizes are available.

2F: 15 5/8" x 7 5/8" x 1 9/16"

4FT: 15 5/8" x 7 9/16" x 3 9/16"

4FE: 15 9/16" x 7 5/8" x 3 9/16"
Also available in 6, 8, 10 & 12" thicknesses.

4F: 15 5/8" x 7 5/8" x 3 9/16"
Available in hollow, semi-solid or solid units.

6F: 15 5/8" x 7 5/8" x 5 9/16"

8F: 15 5/8" x 7 5/8" x 7 9/16"

8FE: 15 9/16" x 7 5/8" x 7 9/16"

8FEFN: 15 9/16" x 7 5/8" x 7 9/16"

10F: 15 5/8" x 7 5/8" x 9 9/16"
Also available in 12" thickness.

44F: 15 5/8" x 3 5/8" x 3 9/16"

8FT: 15 5/8" x 7 9/16" x 7 9/16"

8FETR*: 15 9/16" x 7 9/16" x 7 9/16"
Also available in 2, 4 & 6" thicknesses.
*Specify right or left (right shown)

8FTBN: 15 5/8" x 7 9/16" x 7 9/16"

4 FE 135°: 11 9/16" x 7 5/8" x 3 9/16"
Also available in 8" thickness.

4 FE L CORNER: 15 9/16" x 7 5/8" x 3 9/16"

8UF (v-block): 15 5/8" x 7 5/8" x 7 9/16"

8F8 Solid: 7 5/8" x 7 5/8" x 7 9/16"

8F8 Hollow: 7 5/8" x 7 5/8" x 7 9/16"

KOBB (Open Bottom): 15 5/8" x 7 5/8" x 7 9/16"
Also available in 6, 10 & 12" thicknesses.

FHA (KOBB with Solid Bottom): 15 5/8" x 7 5/8" x 7 9/16"
Also available in 6, 10 & 12" thicknesses.

Code Designations

- F = 1 Face Ground
- FF = 2 Faces Ground
- E = End Ground
- EE = 2 Ends Ground
- V = Vertical Score
- H = Horizontal Score
- BN = Bull Nose
- T = Top Ground
- B = Bottom Ground
- C = Chamfer Ground
- U = Bond Beam

All Trenwyth concrete masonry units are manufactured with an integral water repellent admixture

Chamfers

8FE C1, 8FT C2, 8FET C4, 8FFE C5, 8FEE C11


*Specify right or left (right shown)

Chamfered corners minimize chipping and eliminate sharp corners. Not all chamfer designs are shown. Any side can be chamfered.

Acousta-Wal® Units

Control noise pollution in your project with Acousta-Wal® units.

For more information refer to the Acousta-Wal section of our website.



Scored Units*

V1: 8 x 8 Score

V2: 8 x 5 Score

H1: 4 x 16 Score

Design Your Own

Many scoring patterns are available. We recommend that all scored joints be touchpointed and tooled, particularly in exterior applications.

Detailing to Keep Moisture Out

All exterior mortar joints must contain an approved water repellent.

