

# Split-Face Shapes and Sizes

Note: Not all sizes are shown in this brochure. Please consult your nearest manufacturing facility.

Metric Shapes and Sizes are available.

**Code Designations**

- F = 1 Face Ground
- FF = 2 Faces Ground
- E = End Ground
- EE = 2 Ends Ground
- V = Vertical Score
- H = Horizontal Score
- BN = Bull Nose
- T = Top Ground
- B = Bottom Ground
- C = Chamfer Ground
- U = Bond Beam

All Trenwyth concrete masonry units are manufactured with an integral water repellent admixture

Chamfered corners minimize chipping and eliminate sharp corners. Not all chamfer designs are shown. Any side can be chamfered.


**Chamfers**

\*Specify right or left (right shown)

## SPLIT-FACE/ACOUSTA-WAL® units

Control noise pollution in your project with SPLIT-FACE/ACOUSTA-WAL® units.

Type IV



For more information refer to the Acousta-Wal® section.

## SPLIT-FACE scored units\*

Many scoring patterns are available. We recommend that all scored joints be tuckpointed and tooled, particularly in exterior applications.

## Detailing To Keep Moisture Out

All EXTERIOR MORTAR JOINTS must contain an approved WATER REPELLENT additive such as W.R. Grace DRY-BLOCK® or approved equal.

