

KOHLER® Roughing-In

K-T10333, K-T10334, K-T10335, K-10336 LYNTIER™ RITE-TEMP™ BATH/SHOWER VALVE TRIM

Product Information

Applicable product*:	
Bath/shower valve trim with 1/2" NPT threaded diverter spout	K-T10333-4
Bath/shower valve trim with slip-fit diverter spout	K-T10333-4S
Shower valve trim, less diverter spout	K-T10334-4
Valve only trim	K-T10335-4
NPT diverter bath spout	K-10336
Slip-fit diverter bath spout	K-10336-S
NPT non-diverter bath spout	K-10337
Slip-fit non-diverter bath spout	K-10337-S
* A Rite-Temp valve is required with the specified valve trim.	
Lever handle is ADA compliant.	ADA

Required accessories:

Rite-Temp valve without stops	K-304-K
Rite-Temp valve with stops	K-304-KS
HiFlow Rite-Temp valve with integral stops	K-306-KS
Rite-Temp valve with PVC connections	K-304-KP

Installation Notes

Install the valve trim according to the installation guide.

Install the Rite-Temp or HiFlow Rite-Temp valve according to the installation guide.

Avoid cross-flow conditions. Do not install a shut-off device on either valve outlet.

Cap the shower outlet if the deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install a 7" (17.8 cm) to 18" (45.7 cm) straight pipe or straight tube with single bath elbow between the valve and the wall-mount spout.

