

### Product Information

Applicable faucet trim only:	
Bath and shower cross handle* (shown)	K-T14420-3
Bath and shower lever handle*	K-T14420-4
Shower cross handle*	K-T14421-3
Shower lever handle*	K-T14421-4
Non-diverter valve cross handle*	K-T14423-3
Non-diverter valve lever handle*	K-T14423-4
Shower head, arm and flange	K-14424
35° Bath Spout	K-14426
90° Bath Spout	K-14427

\*Rite-Temp valve must be ordered to complete faucet.

Applicable Rite-Temp valve only:		
Rite-Temp valve without stops	K-304-K	not shown**
Rite-Temp valve with stops	K-304-KS	not shown**
Rite-Temp valve with CPVC female stops	K-304-KP	not shown**
Rite-Temp valve without stops	K-305-K	not shown**

Rite-Temp valve with stops	K-305-KS	not shown**
HiFlow Rite-Temp valve with integral stops	K-306-KS	not shown**
HiFlow Rite-Temp thin wall installation kit	88526	not shown**

\*\*Required for configuration illustrated.

**ADA** Cross and lever handles are ADA compliant

**WARNING: Risk of damage to the K-306-KS valve assembly.** When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

### Installation Notes

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8cm) to 18" (45.7cm) with single elbow between valve and wall-mount spout.

