

KOHLER® Roughing-In

K-T461, K-T462, K-T463, K-304 MEMOIRS® STATELY BATH AND SHOWER FAUCET TRIM

Product Information

Mexico faucets and fittings have an M after the first sequence of numbers (such as K-12345 M).		
Applicable faucet trim only:		
Bath/shower trim, cross handle	K-T461-3S	
Bath/shower trim, faceted lever handle	K-T461-4S	
Bath/shower trim, deco lever handle	K-T461-4V	
Shower trim only, cross handle	K-T462-3S	
Shower trim only, faceted lever handle	K-T462-4S	
Shower trim only, deco lever handle	K-T462-4V	
Valve trim only, cross handle	K-T463-3S	
Valve trim only, faceted lever handle	K-T463-4S	
Valve trim only, deco lever handle	K-T463-4V	
*Rite-Temp valve must be ordered to complete faucet.		
Applicable Rite-Temp valve:		
Rite-Temp valve without stops	K-304-K	not shown
Rite-Temp valve with stops	K-304-KS	not shown
HiFlow Rite-Temp valve with integral stops	K-306-KS	not shown
Rite-Temp valve with PVC connections	K-304-KP	not shown

Lever handles are ADA compliant

ADA

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Install the Rite-Temp valve according to the valve installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

