

KOHLER® Roughing-In

K-T8224, K-T8226, K-T8228, K-304, K-306-KS TABORET® BATH AND SHOWER FAUCET TRIM

Product Information

Applicable faucet trim:		
Bath and shower trim with lever handle*	K-T8224-4	
Bath and shower trim with swirl lever handle*	K-T8224-4A	
Shower only trim with lever handle*	K-T8226-4	
Shower only trim with swirl lever handle*	K-T8226-4A	
Applicable valve trim only:		
With lever handle*	K-T8228-4	
With swirl lever handle*	K-T8228-4A	
* Rite-Temp _™ valve must be ordered to complete faucet.		
Handles are ADA compliant.		ADA
Applicable Rite-Temp _™ valve:		
Without stops	K-304-K-NA	not shown**
With stops	K-304-KS-NA	not shown**
HiFlow valve with integral stops	K-306-KS-NA	not shown**
** Valve system required for configuration illustrated.		

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

All dimensions are nominal and conform to ASME Standard A112.8.1.

