

KOHLER® Roughing-In

K-T14640-4, K-T14641-4, K-T14642-4 CABRIOLE® BATH AND SHOWER FAUCET TRIM

Product Information

Applicable product:	
Bath and shower trim*	K-T14640-4
Shower only trim*	K-T14641-4
Valve only trim*	K-T14642-4
*Rite-Temp® valve must be ordered to complete faucet.	

Applicable Rite-Temp® valve**:	
Rite-Temp® valve without stops OR	K-304-K
Rite-Temp® valve with stops OR	K-304-KS
Hi Flow Rite-Temp® valve with integral stops	K-306-KS
Lever handle is ADA compliant, comply with the actuation force Accessibility Guidelines (Section 309 Operation) of the Americans with Disabilities Act. ADA	
** Required	

Recommended accessories:	
Hi Flow Rite-Temp® thin wall installation kit	88526
Optional accessories:	
Deep roughing-in kit for Rite-Temp® valve (lever handles)	79639

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

