

Product Information

Applicable product*:		
Bath/shower trim, sculpted lever handle, NPT spout	K-T10274-4	not shown
Bath/shower trim, traditional lever handle, NPT spout	K-T10274-4A	not shown
Bath/shower trim, sculpted lever handle, slip-fit spout	K-T10275-4	shown
Bath/shower trim, traditional lever handle, slip-fit spout	K-T10275-4A	shown
Bath/shower trim, script lever handle, slip-fit spout	K-T10275-4G	shown

*Rite-Temp valve must be ordered to complete faucet.

Applicable Rite-Temp valve:		
Rite-Temp valve without stops, NPT connections	K-304-K	not shown
Rite-Temp valve with stops, NPT connections	K-304-KS	not shown

HiFlow Rite-Temp valve with integral stops, NPT connections	K-306-KS	not shown
Rite-Temp valve with PVC connections	K-304-KP	not shown

Lever handles are ADA compliant.



Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Install the Rite-Temp valve according to the valve installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

