

Product Information

Mexico faucets and fittings have an M after the first sequence of numbers (such as K-12345 M)		
Applicable faucet:		
Complete bath and shower faucet with K-304-K Rite-Temp valve and slip-fit spout. (shown)	K-12007-4S	
Bath and shower trim only with lever handle with N.P.T. spout*	K-T12007-4	
Bath and shower trim only with lever handle with slip-fit spout*	K-T12007-4S	
Complete shower faucet with K-304-K Rite-Temp valve. (shown)	K-12014-4	
Valve trim only with lever handle*	K-T12014-4	
Valve trim only with lever handle*	K-T12021-4	
*Rite-Temp valve must be ordered to complete faucet.		
Applicable Rite-Temp valve only:		
Rite-Temp valve without stops	K-304-K	shown**
Rite-Temp valve with stops	K-304-KS	not shown**

HiFlow Rite-Temp valve with integral stops	K-306-KS	not shown**
HiFlow Rite-Temp thin wall installation kit	88526	not shown
**Required for configuration illustrated.		
ADA Lever handle is ADA compliant		

WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Installation Notes

Install this product according to the installation guide. Avoid cross-flow conditions. Do not install shut-off device on either valve outlet. Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet. Install straight pipe or tube drop of 7" (17.8cm) to 18" (45.7cm) with single elbow between valve and wall-mount spout.

