

Product Information

Applicable product:				
Drop-in rim style	K-1124-G			
Fixture*:				
Bathing well				
Basin area bottom	51-3/8" (130.5 cm) x 21" (53.3 cm)			
Basin area top	64-1/2" (163.8 cm) x 30-1/2" (77.5 cm)			
Weight	100 lbs (45.4 kg)			
To overflow				
Water depth	15" (38.1 cm)			
Capacity	72 gal (273 L)			
* Approximate measurements for comparison only.				
Drop-in cutout dimensions:				
70-1/2" (179.1 cm) x 34-1/2" (87.6 cm)				
Blower motor:	Heater	V	Hz	A
1 hp	300 W	120	60	5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Blower motor:	120 V, 15 A, 60 Hz
Blower motor is supplied with a 24" (61 cm) grounding-type plug-in cord.	

Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 41 lbs/square foot (197 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

A blower motor access panel is required.

This product is designed for a drop-in installation only. It is not suited for use in a three-wall alcove with an overhead shower.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7272)

