

Product Information

| | |
|-------------------------------------|-----------|
| Applicable product: | |
| Drop-in bath whirlpool, custom pump | K-1221-CB |
| Drop-in bath whirlpool, custom pump | K-1221-CE |

| | |
|--------------------------|--------|
| Recommended accessories: | |
| Pop-up drain | K-1717 |

| | |
|---|---|
| Fixture*: | |
| Bathing well: | |
| Basin area, bottom | 47" (119.4 cm) x 37" (94 cm) |
| Basin area, top | 67" (170.2 cm) x 42" (106.7 cm) |
| Weight | 120 lbs (54.4 kg) |
| To overflow: | |
| Water depth | 16-7/8" (42.9 cm) |
| Capacity | 122 gal (461.8 L) |
| Drop-in cutout: | 70-1/4" (178.4 cm) x 46-1/4" (117.5 cm) |
| * Approximate measurements for comparison only. | |

| | | | | |
|---------|------|-----|----|-----|
| Pump: | HP | V | Hz | A |
| 1-speed | 1.25 | 120 | 60 | 7.5 |

Required Electrical Service

| | |
|--|--------------------|
| Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI): | |
| Pump/control | 120 V, 15 A, 60 Hz |
| Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump. | |

Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 49 lbs/square foot (238 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

