

Product Information

Applicable product:		
Bath whirlpool, drop-in, custom pump	K-1263-CG	shown
Bath whirlpool, drop-in, custom pump	K-1263-CN	top view shown

Recommended accessories:	
Drain	K-7161-AF

Fixture*:	
Basin area:	
Bathing well	49" (124.5 cm) x 30" (76.2 cm)
Top area	62" (157.5 cm) x 33" (83.8 cm)
To overflow:	
Water depth	17" (43.2 cm)
Capacity	110 gal (416.4 L)
Weight	135 lbs (61.2 kg)
* Approximate measurements for comparison only.	

Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 56 lbs/square foot (274 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

