

### Product Information

Applicable product:	
5' bath whirlpool	K-1337-H
Recommended accessories:	
Drain	K-7166-AF
Fixture*:	
Basin area:	
Bathing well	42" (106.7 cm) x 28" (71.1 cm)
Top area	55" (139.7 cm) x 40" (101.6 cm)
To overflow:	
Water depth	15-1/2" (39.4 cm)
Capacity	73 gal (276.3 L)
Weight	115 lbs (52 kg)
* Approximate measurements for comparison only.	
Pump:	Hp      V      Hz      A
1-speed	1.25    120    60    7.5
Heater:	kW      V      Hz      A
	1.5      120    60    12.5
Included components:	
Cutout template	1017044-7

### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 43 lbs/square foot (208 kg/square meter) loading.

Provide pump/control access in either location shown; supplies must not interfere with pump/control access.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated.

