

### Product Information

Applicable product:	
Bath whirlpool, drop-in, custom pump	K-1201-CB
Product will comply with the Americans with Disabilities Act when installed per the requirements of the Accessibility Guidelines of the Act.	<b>ADA</b>

Recommended accessories:	
Drain	K-7161-AF

Fixture*:	
Basin area:	
Bathing well	42" (106.7 cm) x 17" (43.2 cm)
Top area	55" (139.7 cm) x 25" (63.5 cm)
To overflow:	
Water depth	12-1/8" (30.8 cm)
Capacity	50 gal (189.3 L)
Weight	93 lbs (42.2 kg)
Drop-in cut-out	58-1/2" (148.6 cm) x 28-1/2" (72.4 cm)
* Approximate measurements for comparison only.	

Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7.5

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 43 lbs/square foot (209 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

#### Pump/Control Access

20" (50.8 cm) W x  
15" (38.1 cm) H  
7-1/2" (19.1 cm) Max

