

KOHLER® Roughing-In

K-1126, K-1126-L/R
PROFLEX® 6042
ACRYLIC BATH WHIRLPOOL

Product Information

Applicable product:	
Bath whirlpool, drop-in	K-1126
Bath whirlpool, left drain hole, tile flange	K-1126-L
Bath whirlpool, right drain hole, tile flange	K-1126-R

Recommended accessories:	
Drain	K-11677

Fixture*:	
Basin area:	
Bathing well	46" (116.8 cm) x 21" (53.3 cm)
Top area	55" (139.7 cm) x 31" (78.7 cm)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	57 gal (215.8 L)
Weight	67-1/2 lbs (30.6 kg)
Drop-in cut-out	58-1/4" (148 cm) x 40-1/2" (102.9 cm)
* Approximate measurements for comparison only.	

Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7.5

Optional accessories:	
Separate apron with removable panel for front access	K-1284
20-minute timer kit	K-1717
Jet trim kit (metal finishes)	K-9696

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 33 lbs/square foot (159 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

