

# KOHLER® Roughing-In

K-1460-H2, K-1461-H2  
PORTRAIT®  
6' BATH WHIRLPOOL

## Product Information

Applicable product:	
Bath whirlpool, right drain	K-1460-H2
Bath whirlpool, left drain	K-1461-H2

Required accessories:	
Jet trim kit	K-9696

Fixture*:	
Basin area:	
Bathing well	49-1/2" (125.7 cm) x 26-1/4" (66.7 cm)
Top area	60-1/4" (153 cm) x 29-1/2" (74.9 cm)
To overflow:	
Water depth	17-3/4" (45.1 cm)
Capacity	100 gal (378.5 L)
Weight	145 lbs (65.8 kg)
Drop-in cut-out	70-1/2" (179.1 cm) x 34-1/2" (87.6 cm)
* Approximate measurements for comparison only.	

Pump:	Hp	kW	V	Hz	A
Variable speed	1.5	1.5	240	50/60	11

Recommended accessories:	
Pop-up drain	K-7161-AF

## Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB):	
Pump/control	220/240 V, 20 A, 50/60 Hz

## Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 48 lbs (234 kg).

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

