

Product Information

Applicable product:	
Corner whirlpool, custom pump	K-1433-HE
Corner whirlpool, custom pump	K-1433-HH
Corner whirlpool, custom pump	K-1433-HM

Required accessories:	
Jet trim kit	K-9696
Clearflo pop-up drain	K-7167

Fixture*:	
Basin area:	
Bathing well	45" (114.3 cm) x 25" (63.5 cm)
Top area	66" (167.6 cm) x 33" (83.8 cm)
To overflow:	
Water depth	19" (48.3 cm)
Capacity	112 gal (424 L)
Weight	165 lbs (74.8 kg)
* Approximate measurements for comparison only.	

Drop-in cut-out	59" (149.9 cm) x 59" (149.9 cm) corner installation. Unit must be on job site to determine cut-out radius of contoured front.
Cut-out template	111461-7

Pump:	Hp	kW	V	Hz	A
Variable-speed	1.5	1.5	240	50/60	11

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB):	
Pump/control	220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 44 lbs (216 kg).

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

