

# KOHLER®

## Roughing-In

### K-1487-HF/-HH, K-1487-HM/-HN

#### INFINITY ∞ BATH™

## 5' x 21" CUSTOM BATH WHIRLPOOL

### Product Information

Applicable product:	
Bath whirlpool, custom pump	K-1487-HF
Bath whirlpool, custom pump	K-1487-HH
Bath whirlpool, custom pump	K-1487-HM
Bath whirlpool, custom pump	K-1487-HN

Fixture*:	
Bathing well:	
Basin area	41" (104.1 cm) x 29" (73.7 cm)
Top area	56" (142.2 cm) x 36" (91.4 cm)
To overflow:	
Water depth	15" (38.1 cm)
Capacity	85 gal (321.8 L)
Weight	140 lbs (63.5 kg)
Drop-in cutout	58" (147.3 cm) x 40" (101.6 cm)
* Approximate measurements for comparison only.	

Pump:	Hp	kW	V	Hz	A
Variable-speed	1.5	1.5	240	50/60	11

### Required Electrical Service

Dedicated circuit required, protected with a Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB):	
Pump/control	220/240 V, 20 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 51 lbs (248 kg) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

