

Product Information

Applicable product:	
Bath whirlpool	K-1339-H2
Required accessories:	
Grip rails (pair)	K-9653
Jet trim kit	K-9694
Recommended accessories:	
Pop-up drain	K-7161
Fixture*:	
Basin area:	
Bathing well	47" (119.4 cm) x 27" (68.6 cm)
Top area	64" (162.6 cm) x 29" (73.7 cm)
To overflow:	
Water depth	19-1/2" (49.5 cm)
Capacity	125 gal (473.2 L)
Weight	140 lbs (63.5 kg)
* Approximate measurements for comparison only.	
Drop-in cut-out	71" (180.3 cm) x 39-15/16" (101.4 cm)
Cut-out template	89045-7

Pump:	Hp	kW	V	Hz	A
Variable-speed	2	1.5	240	50/60	15

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB):	
Pump/control	220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 58 lbs (281 kg).

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

