KOHLER®

Features


- Acrylic
- Slotted overflow for maximum bathing depth
- Low threshold height
- Integral lumbar support
- Armrests
- 72" (182.9 cm) x 36" (91.4 cm) x 19" (48.3 cm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ANSI Z124.1.2
- IAPMO/UPC
- Underwriters Laboratories (UL)
- CSA B45
- CSA International

Specified Model



6' (1.8 m) BATH K-1125

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories:

- 0: White
- CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Description **Colors/Finishes** Model K-1125 Drop-in bath 0 Other **Required Accessories** K-7272 Bath drain - above or through-the-floor drain □ CP Other **Optional Accessories** K-9529 Removable bath seat O White

Product Specification:

The acrylic drop-in bath shall be 72" (182.9 cm) in length, 36" (91.4 cm) in width, and 19" (48.3 cm) in height. Bath shall have slotted overflow for maximum bathing depth, low threshold height, and integral lumbar support. Bath shall have armrests. Bath shall be Kohler Model K-1125-____.

ARCHER

Technical Information

Fixture*:	
Bathing well	
Basin area	51-3/8" (130.4 cm) x 21" (53.3 cm)
Top area	64-1/2" (163.8 cm) x 30-1/2"
	(77.5 cm)
Weight	70 lbs (31.7 kg)
To overflow	
Water depth	15″ (38.1 cm)
Capacity	72 gal (273 L)
* Approximate measurements for comparison only.	
Drop-in cutout dimensions:	
70-1/2" (179.1 cm) x 34-1/2" (87.7 cm)	

Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 39 lbs/square foot (189 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

This bath is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

No change in measurements if connected with drain illustrated. (K-7272)

