

KOHLER® Roughing-In

K-1195, K-1195-L/R, K-1199, K-1199-L/R
SYNCHRONY®
6' BATH

Product Information

Applicable product:	
Bath with Softgrip grip handles, drop-in	K-1199
Bath with Softgrip grip handles, left drain, integral flange	K-1199-L
Bath with Softgrip grip handles, right drain, integral flange	K-1199-R
Bath less Softgrip grip handles, drop-in	K-1195
Bath less Softgrip grip handles, left drain, integral flange	K-1195-L
Bath less Softgrip grip handles, right drain, integral flange	K-1195-R
Recommended accessories:	
Drain	K-7161-AF

Fixture*:	
Basin area:	
Bathing well	49" (124.5 cm) x 25" (63.5 cm)
Top area	61" (154.9 cm) x 34" (86.4 cm)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	72 gal (272.5 L)
Weight	80 lbs (36.3 kg)
Drop-in cut-out	70" (177.8 cm) x 40" (101.6 cm)
* Approximate measurements for comparison only.	

Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 34 lbs/square foot (164 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

The apron must be installed before the finished floor and wall materials are installed.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

