

KOHLER®

Roughing-In

K-1714-NA, K-1715-NA, K-1697-NA, K-1716-NA
STEAM GENERATOR

Product Information

Applicable product:	
18 kW steam generator	K-1714-NA
22 kW steam generator	K-1715-NA
26 kW steam generator	K-1697-NA
30 kW steam generator	K-1716-NA

Water and drain requirements:	
Water supply	3/8" copper line, 3/8" NPT female thread
Steam line	1/2" copper line 1/2" NPT female thread
Pressure relief valve	3/4" NPT female thread, valve supplied
Drain line	3/8" copper line, 3/8" NPT female thread, ball valve supplied
Generator:	
Weight	40 lbs (18.1 kg) each, 80 lbs (36.2 kg) total

Required Electrical Service

Two dedicated circuits required:	
Steam generator - 18 kW	240 V, 50 A, 50/60 Hz
Steam generator - 22, 26 kW	240 V, 70 A, 50/60 Hz
Steam generator - 30 kW	240 V, 100 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Fixture dimensions are nominal.

For this steam generator, do not exceed the maximum rating volume.

To determine the appropriate model for your installation, determine the cubic feet of your steam area by multiplying L x W x H. Compare the total to chart in the specification sheet and use the closest match. Always round up. For every foot of ceiling height over 8' (2.45 m) use the next larger steam unit.

Minimum required access is 20" (50.8 cm)
L x 13" (33" cm) H x 6-1/2" (16.5 cm) W.

