

Product Information

Applicable product:	
Elongated front (left-hand trip lever), 1.6 gpf (6 lpf) or 1.28 gpf (4.8 lpf)	K-3496
Elongated front (left-hand trip lever), 1.28 gpf (4.8 lpf)	K-3496-HE
Elongated front (right-hand trip lever)	K-3496-RA
Product is ADA compliant when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. ADA	

Fixture:	
Configuration	Two-piece, elongated
Water per flush	1.6 gal (6 L) or 1.28 gal (4.8 L)
Passageway	2-1/8" (5.4 cm)
Water area	11-3/4" (29.8 cm) x 9-1/4" (23.5 cm)
Water depth from rim	5-7/8" (14.9 cm)
Seat post hole centers	5-1/2" (14 cm)

Included components:	
Bowl	K-4286
Tank cover	1015867
Trip lever, left-hand	1059436
Trip lever, right-hand	1036058
Bolt cap accessory pack	1013092
Tank accessory pack	1016548
Tank, left-hand trip lever, 1.6 gpf (6 lpf) or 1.28 gpf (4.8 lpf)	K-4634
Tank, left-hand trip lever, 1.28 gpf (4.8 lpf)	K-4634-HE
Tank, right-hand trip lever, 1.6 gpf (6 lpf) or 1.28 gpf (4.8 lpf)	K-4634-RA

Installation Notes

Install this product according to the installation guide.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2.

This toilet is ADA compliant when an open front seat is installed.

