SYMPTOMS	CORRECTIVE ACTION	PARTIAL SERVICE PARTS
1. Poor flush.	A. Adjust the tank water level to match the waterline.     B. Fully open the water supply shut-off valve.     C. Clear obstructions from the trapway, jet, or bowl rim holes.     D. Clear obstructions from the waste line.	1034693** (LH) 1036058** (RH) 1057940 Hose Cap 78132 51261 Clip
2. No flush.	A. Reconnect the flapper chain to the trip lever or flush valve.     B. Adjust the flapper chain assembly to remove excess slack.	Seal Waterline
3. The fill valve turns on/off by itself without the toilet being flushed, or it runs allowing water to enter the tank.	A. Adjust the flapper chain for proper slack so the flapper closes. B. Clean or replace the flapper if it is worn, dirty, or misaligned with the opening. C. Clean the area around the opening to allow the flapper to seal. D. Remove the tank and tighten the flush valve nut if flush valve gasket is leaking. Do not overtighten. If leakage continues, replace the gasket. E. Adjust the tank water level if it is too high. F. Replace the fill valve if the valve float sinks.	Fill Valve 85307 Washer 1016219 Flapper Washer 1057941 Locknut 1016219 Flush Valve 42397 Nut 1018165-A Nut 1018165-A
4. Tank takes excessive time to fill.	A. Fully open the water supply shut-off valve.     B. Clean the valve inlet, valve head, or supply line. Flush the lines.	
5. There is excessive noise when the tank is filling.	A. Partially close the water supply shut-off valve if the water pressure to the toilet is too high. Check the toilet performance following any such adjustment.     B. Remove dirt or obstructions from the valve head. Flush the lines.	Gasket  1014065 Attachment Plate  1024390 Accessory Pack (2 ea.)
IMPORTANT: Use only genuine Kohler parts as shown to avoid property damage.		**Finish/color code required.
If unable to correct the problem, contact Customer Service: 1-800-4-KOHLER (USA), 1-800-964-5590 (Canada), or www.kohler.com.		

1066504-6-**A** ©2007 Kohler Co.