SYMPTOMS	CORRECTIVE ACTION	PARTIAL SERVICE PARTS
1. Poor flush.	A. Adjust tank water level to match the waterline.     B. Fully open water supply shut-off valve.     C. Clear obstruction in trapway, jet, or bowl rim holes.     D. Clear obstruction in soil pipe or vent pipe.	78132 Nut 1057940 Valve 85085** (LH) 1007913** (RH)
2. No flush.	A. Reconnect the flapper chain to the trip lever or flush valve.     B. Adjust flapper chain assembly to remove excess slack.	Trip Lever 52156 83143 Hose Seal 51261
3. Fill valve turns on/off by itself without toilet being flushed, or runs allowing water to enter tank.	<ul> <li>A. Adjust flapper chain for proper slack so flapper is not held off flush valve seat.</li> <li>B. Clean or replace flapper if flapper is worn, dirty, or misaligned with flush valve seat or flush valve seat is damaged. Replace flush valve seal or flush valve.</li> <li>C. Remove tank and tighten flush valve nut if flush valve gasket is leaking. Do not overtighten. If leakage continues, replace gasket.</li> <li>D. Clean fill valve seat/seat washer of debris, or replace piston/seat washer assembly.</li> <li>E. Replace fill valve if valve float sinks.</li> <li>F. Adjust tank water level if too high.</li> </ul>	Clip Waterline  1060196 Fill Valve 85307 Washer  Clip Waterline  1015139 Flush Valve 85160 Flapper 53154
4. Long tank fill cycle.	A. Fully open water supply shut-off valve.     B. Clean fill valve inlet, valve head, or supply line. Flush lines.	1057941 Washer 51487 Gasket
5. Noisy tank fill cycle.	A. Partially close the water supply shut-off valve if water pressure to the toilet is too high. Check toilet performance following any such adjustment.     B. Remove dirt or obstruction in valve head, flush line.	Washer
IMPORTANT: Use only genuine Kohler parts as shown to avoid property damage.		**Finish/color code required.
If unable to correct the problem, contact Customer Service: 1-800-4-KOHLER (USA), 1-800-964-5590 (Canada), or www.kohler.com.		

1015136-6-**C** ©2006 Kohler Co.