

Product Information

Applicable product:	
60" (152.4 cm) vanity	K-2437
Recommended lavatories:	
Fountainhead above-the-counter or self-rimming cast iron lavatory	K-2829
Fountainhead countertop cast iron lavatory	K-2834
Fountainhead above-the-counter marble lavatory	K-2352
Recommended accessories:	
21" (53.3 cm) wall storage	K-2431
21" (53.3 cm) wall storage – designed for integral faucet with lever handle	K-2432
Swivel vanity seat	K-2438
Shelf for integral faucet with handle	K-2440
Angle-poise mirror	K-2441

Required Electrical Service

Two (2) electrical supply outlets are required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Receptacle:	120 V, 15 A, 60 Hz
Lighting:	
Two (2) puck lights	5 W

Installation Notes

Install this product according to the installation guide.

Select the type of fastener based on the wall material. A minimum of 50 lbs (22.68 kg) load bearing fastener is recommended.

A vessel style lavatory is the only style accepted for this vanity.

Up to two (2) vessel style lavatories may be installed to this vanity.

Two (2) electrical supply outlets are required for this installation.

To allow the user to access the touch switch to activate the lighting, a minimum of 2" (5.1 cm) of clearance is required on the far left side.

