

### Product Information

Applicable product:	
Elongated bowl toilet	K-4368
Elongated bowl toilet with 4 bolt holes in base	K-4368-B
Elongated bowl toilet with bedpan lugs	K-4368-L
Fixture is ADA compliant. <b>ADA</b>	

Fixture:	
Configuration	Top spud, elongated
Water per flush	1.6 gal (6 L)*
Spud size	1-1/2"
Passageway	2-1/4" (5.7 cm)
Water area	11-3/8" (28.9 cm) x 10-3/8" (26.4 cm)
Water depth from rim	6" (15.2 cm)
Seat post hole centers	5-1/2" (14 cm)
* Designed to flush with 1.6 gal (6 L) of water when installed with a 1.6 gpf (6 lpf) valve.	

Recommended accessories:	
Lustra™ open front seat with support arms and cover	K-4654
Lustra open front seat with support arms and cover with anti-microbial agent	K-4654-A
Lustra open front seat	K-4670-C
Lustra open front seat with anti-microbial agent	K-4670-CA

Included components:	
Spud	18357
Bolt cap accessory pack	52048

### Installation Notes

Install this product according to the installation guide.

Refer to manufacturer and local codes for flush valve requirements: for 12" (30.5 cm) rough-in, sweat extension nipple is required.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2.

