

Product Information

Applicable product:	
Wall-mount lavatory	K-2475
Required component:	
Supply fitting	K-7482 required*
* Required for configuration illustrated.	
Recommended accessories:	
Faucet	K-7842
Support bolt (if required), for use with "cold water supply" only	K-2480-A
Fixture*:	
Basin area	11" (27.9 cm) x 9" (22.9 cm)
Water depth	5-5/8" (14.3 cm)
Drain hole (without spud)	2-1/4" (5.7 cm) D.
Faucet hole	1-1/2" (3.8 cm) D.
Spud hole (without spud)	1-1/8" (2.9 cm) D.
* Approximate measurements for comparison only.	

Included components:	
1-1/2" drain hole spud	18357
Inlet spud	31686

Installation Notes

Install this product according to the installation guide.

The drain hole spud for slipping in 1-1/2" OD tubing is also available with 1-1/2" NPT straight outside thread.

The supply fitting for a regularly furnished wall is not to exceed 1" (2.5 cm) thick. For thicker walls add 1" (2.5 cm) to the supply measurement 3" (7.6 cm) for every inch or fraction of additional wall thickness.

Required hardware and accessories are shown.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2.

