



moonstone flush mounts	series#	lampping	dimensions	finishes	options
17"Φ 	16-3	3 x 6OW A19 inc. (med.) (glass diffuser only)	W = 17" H = 6.3"	24 30 14 O2 95	A17 Acrylic bowl
	16-4	3 x 13W quad cfl. (G24q-1)			
13"Φ 	16-1	2 x 6OW A19 inc. (med.) (glass diffuser only)	W = 13" H = 5.1"	24 30 14 O2 95	A13 Acrylic bowl
	16-2	2 x 13W quad cfl. (G24q-1)			

general specifications

- Cold rolled steel fittings, housing and trim.
- Glass diffusers are standard.
- Glass diffusers are 3/8" opal white pressed glass.
- Acrylic diffusers are 3/16" white acrylic with matte exterior finish.
- All items U.L and C.U.L. approved for dry locations.
- Fluorescent ballasts are electronic HPF, program start, universal voltage (120V to 277V).
- All units mount to standard 4" octagonal junction box. No additional supports required.
- Visit www.oxygenlighting.com for technical cut sheets.
- Oxygen reserves the right to modify designs at any time.
- Custom modifications are available upon request.

sample catalog number

series #	finish	options	catalog number
16-4	24	A17	16-4-24-A17
moonstone series, 17" glass bowl, flush mount, 3x13W	satin nickel finish	17" acrylic bowl in place of glass bowl	

