




saturna flush mounts		series#	lampping	dimensions	finishes	options
22"Φ 	15-5	4 x 6OW A19 inc. (med.) (glass diffuser only)	D = 22.5" H = 7.8"	24 30 14 O2 95	satin nickel satin brass polished chrome polished brass old world	A22 Acrylic bowl
	15-6	4 x 13W quad cfl. (G24q-1)				
17"Φ 	15-3	3 x 6OW A19 inc. (med.) (glass diffuser only)	D = 17" H = 6.3"	24 30 14 O2 95	satin nickel satin brass polished chrome polished brass old world	A17 Acrylic bowl
	15-4	3 x 13W quad cfl. (G24q-1)				
	15-19	2 X 26W quad cfl. (G24q-3)				EM* Integral emergency ballast (Series 15-19 only)
13"Φ 	15-1	2 x 6OW A19 inc. (med.) (glass diffuser only)	D = 13" H = 5.1"	24 30 14 O2 95	satin nickel satin brass polished chrome polished brass old world	A13 Acrylic bowl
	15-2	2 x 13W quad cfl. (G24q-1)				

general specifications

- Cold-rolled housing and trim.
- Glass diffusers are standard.
- Glass diffusers are 3/8" opal white pressed glass.
- Acrylic diffusers are 3/16" white acrylic with matte exterior finish.
- All items U.L and C.U.L. approved for dry locations.
- Fluorescent ballasts are electronic HPF, program start, universal voltage (120V to 277V).
- All units mount to 4" octagonal junction box.
- Visit www.oxygenlighting.com for technical cut sheets.
- Oxygen reserves the right to modify designs at any time.

* • Unless otherwise specified, a Bodine ballast will be used. Only EM ballasts that match an "F-Can" hole pattern may be installed.



sample catalog number

series #	finish	options	catalog number
15-4	- 24	- A17	= 15-4-24-A17
saturna series, 17" glass bowl, flush mount 3x13W quad	satin nickel finish	17" acrylic bowl in place of glass bowl	

