





type

sunfire flush mounts	series#	lampping	dimensions	finishes	options
	<b>17-5</b>	4 x 60W A19 inc. (med.) (glass diffusers only)	D = 22.5" H = 7.8"	<b>24</b> <b>30</b> <b>14</b> <b>O2</b> <b>95</b>	<b>A22</b> Acrylic bowl
	<b>17-6</b>	4 x 13W quad cfl. (G24q-1)			
	<b>17-3</b>	3 x 60W A19 inc. (med.) (glass diffusers only)	D = 17" H = 6.3"	<b>24</b> <b>30</b> <b>14</b> <b>O2</b> <b>95</b>	<b>A17</b> Acrylic bowl
	<b>17-4</b>	3 x 13W quad cfl. (G24q-1)			
	<b>17-19</b>	2 X 26W quad cfl. (G24q-3)			
	<b>17-1</b>	2 x 60W A19 inc. (med.) (glass diffusers only)	D = 13" H = 5.1"	<b>24</b> <b>30</b> <b>14</b> <b>O2</b> <b>95</b>	<b>A13</b> Acrylic bowl
	<b>17-2</b>	2 x 13W quad cfl. (G24q-1)			

general specifications

- Cast steel fittings.
  - Cold-rolled housing and trim.
  - Glass diffusers are standard.
  - Glass diffusers are 3/8" opal white pressed glass.
  - Acrylic diffusers are 3/16" white acrylic with matte exterior finish.
  - All items U.L and C.U.L. approved for dry locations.
  - Fluorescent ballasts are electronic HPF, program start, universal voltage (120V to 277V).
  - All units mount to 4" octagonal junction box.
  - Visit [www.oxygenlighting.com](http://www.oxygenlighting.com) for technical cut sheets.
  - Oxygen reserves the right to modify designs at any time.
- \* Unless otherwise specified, a Bodine ballast will be used. Only EM ballasts that match an "F-Can" hole pattern may be installed.



sample catalog number

series #	finish	options	catalog number
<b>17-4</b>	<b>24</b>	<b>A17</b>	<b>17-4-24-A17</b>
sunfire series, 17" glass bowl, flush mount 3x13W quad	satin nickel finish	17" acrylic bowl in place of glass bowl	

