oxygen ADA sconces

series#	lamping	dimensions	diffuser		finishes		options
2-597	1 x 26W quad 4-pin fluorescent (G24Q-3)	W = 7" H = 16.75" E = 4"	fabric	24 14 30 95	satin nickel polished chrome stain brass old world		
2-5129	1 x 60W T10 incandescent (medium)						
	2-597	2-597 1 x 26W quad 4-pin fluorescent (G24Q-3)	2-597 1 x 26W quad 4-pin fluorescent $W = 7$ " $H = 16.75$ " $E = 4$ "	2-597 1 x 26W quad 4-pin fluorescent W = 7" H = 16.75" E = 4" fabric	2-597 1 x 26W quad 4-pin fluorescent W = 7" Fabric 24 14 30 95	2-597 $1 \times 26W$ quad 4-pin fluorescent $W = 7$ " $H = 16.75$ " $E = 4$ " fabric 24 satin nickel polished chrome stain brass old world	2-597 1 x 26W quad 4-pin fluorescent W = 7" Fabric Satin nickel polished chrome stain brass old world W = 7" Fabric Satin nickel polished chrome stain brass old world Satin practice Satin nickel polished chrome stain brass old world Satin nickel polished chrome stain brass old

- Clear, polished resin accent.
- Cast steel fittings.
- Cold-rolled steel backplate.
- Shade is white cotton fabric.
- U.L and C.U.L. approved for dry locations.
- Fluorescent ballast is electronic HPF, program start, universal voltage (120V to 277V).
- \bullet All units mount to 4" octagonal junction box.
- Visit www.oxygenlighting.com for technical cut sheets.
- Oxygen lighting reserves the right to modify designs at any time.

sample	catalog	number







ADA-52