

type

haiku sconce	series#	lampping	dimensions	diffuser	finishes	options
	<b>2-570</b>	1 x 18W twin 4-pin fluorescent (2G11)*	W = 12" H = 11.5" D = 4"	<b>1</b> glass <b>2</b> white acrylic <b>3</b> tobacco acrylic <b>4</b> faux onyx acrylic <b>6</b> silver cloth acrylic <b>7</b> wave acrylic <b>8</b> leaf acrylic	<b>24</b> satin nickel <b>30</b> satin brass <b>14</b> polished chrome <b>02</b> polished brass <b>95</b> old world	<b>H</b> 277V ballast

**general specifications**

- Cast steel trim.
- Cold rolled steel housing.
- Acrylic top lens.
- Acrylic diffusers are 1/8" thick, finish as specified.
- Glass diffusers are 1/4" thick satin white duplex glass.
- All items U.L and C.U.L. approved for dry locations.
- Fluorescent ballast is electronic, HPF instant start, 120V (for 277V, specify "H" option).
- All units mount to standard 4" octagonal junction box. Unless otherwise noted, no additional supports required.
- Visit [www.oxygenlighting.com](http://www.oxygenlighting.com) for technical cut sheets.
- Oxygen lighting reserves the right to modify designs at any time.

\* **To avoid possible abnormal end of life, use lamps with integral End of Life protection.**

**optional diffuser finishes**



**sample catalog number**

series #	diffuser	finish	options	catalog number
<b>2-570</b>	<b>- 1</b>	<b>30</b>	<b>-</b>	<b>= 2-570-130</b>
haiku sconce, 18W twin 4-pin	satin white duplex glass	satin brass	none	

